


1 OPEN PLAN OFFICE SPACE

Frosted Louver with 200lm/ft direct and 500lm/ft uplight - 44ft length

Room Size:	50'x50'
Ceiling height:	10'
Luminaire mounting height:	8'5"
Reflectances:	80/50/20
Light loss factor:	1.0

Workplane 30" above finished floor (fc level)	45
Ceiling uniformity maximum to minimum	6:1
UGR average	<12
Watt sq/ft	0.352




2 SINGLE OFFICE SPACE

Frosted Louver with 400lm/ft direct and 250lm/ft uplight - 8ft length

Room Size:	10'x10'
Ceiling height:	10'
Luminaire mounting height:	8'5"
Reflectances:	80/50/20
Light loss factor:	1.0

Workplane 30" above finished floor (fc level)	35
Ceiling uniformity maximum to minimum	3:1
UGR average	<12
Watt sq/ft	0.4




3 CLASSROOM SPACE

Over Desk: Frosted Louver with 200lm/ft direct and 500lm/ft uplight - 32ft length White-Board: Frosted Louver with 400lm/ft direct - 12ft length

Room Size:	24'x40'
Ceiling height:	10'
Luminaire mounting height:	8'5"
Reflectances:	80/50/20
Light loss factor:	1.0

Workplane 30" above finished floor (fc level)	44
Average illuminance on White-board wall	36
Ceiling uniformity maximum to minimum	7:1
UGR average	<13
Watt sq/ft	0.375



^{*}all data is based on Diffused Light Diffuser (DD3)