


## 1 OPEN PLAN OFFICE SPACE

#### Diffused light diffuser PW03 option with 200lms/ft direct and 400lms/ft indirect

Room Size	50'x50'	Workplane 30" above finished floor (fc level)	42
Ceiling height	12'	Workplane uniformity max to min	1.2 to 1
Luminaire mounting height	10'	Ceiling uniformity max to min	3.5:1
Reflectances	80/50/20	UGR average	<12
Light loss factor	1.0	Watt sq/ft	0.4




## 2 CONFERENCE ROOM

#### Diffused light diffuser PW01 option with 400lms/ft direct and 600lms/ft indirect

Room Size	20'x12'	Worl
Ceiling height	10'	Wat
Luminaire mounting height	8'6"	
Reflectances	80/50/20	
Light loss factor	1.0	

Workplane 30" above finished floor (fc level) 44
Watt sq/ft 0.45




## 3 LIBRARY

Diffused light diffuser PW02 option over reading area with 200lms/ft direct and 600lms/ft indirect Diffused light diffuser PW02 option in book stack area with 400lms/ft direct and 200lms/ft indirect

Room Size	40'x40'
Ceiling height	12'
Book stack height	5′
Luminaire mounting height	9'
Reading area - for Stacks	8′
Reflectances	80/50/20
Light loss factor	1.0

Reading Area Workplane 30" above finished	44
Workplane uniformity max to min	1.2 to 1
Illuminance on book stacks	25
Ceiling uniformity max to min	4:1
Watt sq/ft	0.54






# 1 OPEN PLAN OFFICE SPACE

Widespread diffuser PW02 option with 400lms/ft direct and 400lms/ft indirect

Room Size	50'x50'	Workplane 30" above finished floor (fc level)	43
Ceiling height	12'	Workplane uniformity max to min	1.2 to 1
Luminaire mounting height	9'6"	Watt sq/ft	0.38
Reflectances	80/50/20	UGR average	<17
Light loss factor	1.0	Ceiling uniformity max to min	6:1




## 2 CONFERENCE ROOM

Widespread diffuser PW01 option with 400lms/ft direct and 600lms/ft indirect

Room Size	20'x12'
Ceiling height	10'
Luminaire mounting height	7'6"
Reflectances	80/50/20
Light loss factor	1.0

Workplane 30" above finished floor (fc level) 44

Watt sq/ft 0.45



## 3 LIBRARY

Widespread diffuser PW03 option over reading area with 600lms/ft direct and 200lms/ft indirect Diffused light diffuser PW03 option in book stack area with 400lms/ft direct and 200lms/ft indirect

Room Size	40'x40'
Ceiling height	12'
Book stack height	5′
Luminaire mounting height	8′
Reflectances	80/50/20
Light loss factor	1.0

Reading Area Workplane 30" above finished	45
Workplane uniformity max to min	1.1 to 1
Illuminance on book stacks	24
Ceiling uniformity max to min	2:1
Watt sq/ft	0.43

