

**1 PERFORMANCE DATA**

**DIRECT FROSTED LOUVER WITH ASSYMETRIC LENS (DD1)**

	LUMEN/FT	WATT/FT	LPW
1200	1200	13	111
1000	1000	9	115
800	800	7	119
700	700	6	122
600	600	5	123
500	500	4	124
400	400	3	125
300	300	3	125
200	200	2	132

**DIRECT FROSTED LOUVER WITH COMFORT LENS (DD4)**

	LUMEN/FT	WATT/FT	LPW
1200	1200	13	101
1000	1000	9	107
800	800	7	109
700	700	6	111
600	600	5	115
500	500	4	115
400	400	3	115
300	300	3	116
200	200	2	121

**DIRECT BLACK LOUVER WITH COMFORT LENS (DD4)**

	LUMEN/FT	WATT/FT	LPW
500	500	13	40
400	400	9	42
300	300	7	43
200	200	5	45
100	100	2	47

**DIRECT SATIN CHROME LOUVER WITH COMFORT LENS (DD4)**

	LUMEN/FT	WATT/FT	LPW
800	800	13	60
700	700	11	60
600	600	9	63
500	500	7	65
400	400	5	68
300	300	3	68
200	200	3	68
100	100	2	69

**DIRECT SATIN GOLD LOUVER WITH COMFORT LENS (DD4)**

	LUMEN/FT	WATT/FT	LPW
800	800	13	59
700	700	11	59
600	600	9	62
500	500	7	63
400	400	5	66
300	300	3	66
200	200	3	66
100	100	2	68

**DIRECT SATIN CHAMPAGNE LOUVER COMFORT LENS (DD4)**

	LUMEN/FT	WATT/FT	LPW
800	800	13	60
700	700	11	60
600	600	9	63
500	500	7	65
400	400	5	68
300	300	3	68
200	200	3	68
100	100	2	69

**INDIRECT BATWING (UD1)**

	LUMEN/FT	WATT/FT	LPW
1600	1600	13	129
1200	1200	9	137
1000	1000	7	140
750	750	5	146
500	500	3	147
250	250	2	152

**INDIRECT ASYMMETRIC (UD3)**

	LUMEN/FT	WATT/FT	LPW
1200	1200	13	97
1000	1000	10	100
750	750	8	103
500	500	5	107
250	250	2	112