



1 PERFORMANCE DATA

DIRECT COMFORT (DD4)




| LUMEN/FT | WATT/FT | LPW |
|----------|---------|-----|
| 1400 | 13 | 103 |
| 1200 | 11 | 106 |
| 1000 | 9 | 109 |
| 800 | 7 | 112 |
| 600 | 5 | 115 |
| 400 | 3 | 119 |
| 200 | 2 | 120 |

DIRECT BATWING (DD2)




| LUMEN/FT | WATT/FT | LPW |
|----------|---------|-----|
| 1400 | 13 | 108 |
| 1200 | 11 | 112 |
| 1000 | 9 | 115 |
| 800 | 7 | 118 |
| 600 | 5 | 121 |
| 400 | 3 | 124 |
| 200 | 2 | 129 |

DIRECT ASYMMETRIC (DD1)




| LUMEN/FT | WATT/FT | LPW |
|----------|---------|-----|
| 1400 | 13 | 112 |
| 1200 | 11 | 115 |
| 1000 | 9 | 118 |
| 800 | 7 | 121 |
| 600 | 5 | 125 |
| 400 | 3 | 128 |
| 200 | 2 | 133 |

INDIRECT BATWING (UD1)



| LUMEN/FT | WATT/FT | LPW |
|----------|---------|-----|
| 1650 | 13 | 132 |
| 1400 | 10 | 137 |
| 1200 | 9 | 140 |
| 1000 | 7 | 144 |
| 800 | 6 | 146 |
| 600 | 4 | 150 |
| 400 | 3 | 153 |
| 200 | 1 | 153 |

INDIRECT ASYMMETRIC (UD3)



| LUMEN/FT | WATT/FT | LPW |
|----------|---------|-----|
| 1200 | 13 | 97 |
| 1000 | 10 | 100 |
| 800 | 9 | 102 |
| 600 | 6 | 107 |
| 400 | 4 | 109 |
| 200 | 2 | 112 |