

**1** PERFORMANCE DATA

**DIRECT FROSTED LOUVER WITH COMFORT LENS (DD4)**

	LUMEN/FT	WATT/FT	LPW
	1200	13	101
	1000	9	107
	800	7	109
	700	6	111
	600	5	115
	500	4	115
	400	3	115
	300	2	116
	200		121

**DIRECT BLACK LOUVER WITH COMFORT LENS (DD4)**

	LUMEN/FT	WATT/FT	LPW
	500	13	40
	400	9	42
	300	7	43
	200	5	45
	100	2	47

**DIRECT SATIN CHROME LOUVER WITH COMFORT LENS (DD4)**

	LUMEN/FT	WATT/FT	LPW
	800	13	60
	700	11	60
	600	9	63
	500	7	65
	400	5	68
	300	3	68
	200	3	68
	100	2	69

**DIRECT SATIN GOLD LOUVER WITH COMFORT LENS (DD4)**

	LUMEN/FT	WATT/FT	LPW
	800	13	59
	700	11	59
	600	9	62
	500	7	63
	400	5	66
	300	3	66
	200	3	66
	100	2	68

**DIRECT SATIN CHAMPAGNE LOUVER WITH COMFORT LENS (DD4)**

	LUMEN/FT	WATT/FT	LPW
	800	13	60
	700	11	60
	600	9	63
	500	7	65
	400	5	68
	300	3	68
	200	3	68
	100	2	69

**INDIRECT OPAL (UD2)**

	LUMEN/FT	WATT/FT	LPW
	1600	13	128
	1200	9	132
	1000	7	136
	750	5	144
	500	3	144
	250	2	147

**INDIRECT ASYMMETRIC (UD3)**

	LUMEN/FT	WATT/FT	LPW
	1200	13	97
	1000	10	100
	750	8	103
	500	5	107
	250	2	112