



1 PERFORMANCE DATA


1.5 DIRECT DIFFUSED (DD3 AND DS3)

	LUMEN/FT	WATT/FT	LPW
	1000	9	109
	800	7	112
	600	5	116
	400	3	119
	200	2	121


2.5 DIRECT DIFFUSED (DD3 AND DS3)

	LUMEN/FT	WATT/FT	LPW
	1400	13	122
	1200	11	126
	1000	9	131
	800	7	132
	600	5	136
	400	3	141
	200	2	143


3.5 DIRECT DIFFUSED (DD3 AND DS3)

	LUMEN/FT	WATT/FT	LPW
	1400	13	130
	1200	11	134
	1000	9	137
	800	7	141
	600	5	145
	400	3	149
	200	2	151


INDIRECT BATWING (UD1)

	LUMEN/FT	WATT/FT	LPW
	1650	13	132
	1400	10	137
	1200	9	140
	1000	7	144
	800	6	146
	600	4	150
	400	3	153
	200	1	153

INDIRECT ASYMMETRIC (UD3)

	LUMEN/FT	WATT/FT	LPW
	1200	13	97
	1000	10	100
	800	9	102
	600	6	107
	400	4	109
	200	2	112

INDIRECT OPAL DIFFUSER (UD2)

	LUMEN/FT	WATT/FT	LPW
	1650	13	128
	1400	11	132
	1200	9	135
	1000	7	139
	800	6	141
	600	4	144
	400	3	147
	200	1	150