











1 PERFORMANCE DATA


1.5 DIRECT DIFFUSED (DD3)	LUMEN/FT	WATT/FT	LPW	1.5 DIRECT DIFFUSED (DD3) REGRESSED	LUMEN/FT	WATT/FT	LPW
	800	9	93		800	10	79
	600	7	94		600	7	83
	400	5	98		400	5	88
	200	2	103		200	2	94

2.5 DIRECT DIFFUSED (DD3)	LUMEN/FT	WATT/FT	LPW	2.5 DIRECT DIFFUSED (DD3) REGRESSED	LUMEN/FT	WATT/FT	LPW
	1200	13	104		1000	11	90
	1000	11	107		800	9	93
	800	8	110		600	6	95
	600	6	114		400	4	99
	400	4	117		200	2	105
	200	2	122				

2.5 DIRECT COMFORT (DD4)	LUMEN/FT	WATT/FT	LPW	2.5 DIRECT COMFORT (DD4) REGRESSED	LUMEN/FT	WATT/FT	LPW
	1200	13	88		1000	13	79
	1000	11	90		800	9	81
	800	9	93		600	7	83
	600	7	95		400	5	88
	400	4	100		200	2	91
	200	2	104				

3.5 DIRECT DIFFUSED (DD3)	LUMEN/FT	WATT/FT	LPW	3.5 DIRECT DIFFUSED (DD3) REGRESSED	LUMEN/FT	WATT/FT	LPW
	1400	13	110		1200	13	95
	1200	11	114		1000	11	98
	1000	8	116		800	8	100
	800	7	119		600	7	103
	600	5	123		400	4	107
	400	3	127		200	2	114
	200	2	129				

INDIRECT BATWING (UD1)	LUMEN/FT	WATT/FT	LPW	INDIRECT ASYMMETRIC (UD3)	LUMEN/FT	WATT/FT	LPW
	1200	11	116		1000	11	82
	1000	9	119		800	9	84
	800	7	122		600	7	89
	600	5	130		400	4	91
	400	3	137		200	2	95
	200	1	144				

INDIRECT OPAL DIFFUSER (UD2)	LUMEN/FT	WATT/FT	LPW
	1000	11	98
	800	9	100
	600	6	106
	400	3	112
	200	2	113