











**1 PERFORMANCE DATA**


1.5 DIRECT DIFFUSED (DD3)	LUMEN/FT	WATT/FT	LPW	1.5 DIRECT DIFFUSED (DD3) REGRESSED	LUMEN/FT	WATT/FT	LPW
	800 600 400 200	9 7 5 2	93 94 98 103		800 600 400 200	10 7 5 2	79 83 88 94

2.5 DIRECT DIFFUSED (DD3)	LUMEN/FT	WATT/FT	LPW	2.5 DIRECT DIFFUSED (DD3) REGRESSED	LUMEN/FT	WATT/FT	LPW
	1200 1000 800 600 400 200	13 11 8 6 4 2	104 107 110 114 117 122		1000 800 600 400 200	11 9 6 4 2	90 93 95 99 105

2.5 DIRECT COMFORT (DD4)	LUMEN/FT	WATT/FT	LPW	2.5 DIRECT COMFORT (DD4) REGRESSED	LUMEN/FT	WATT/FT	LPW
	1200 1000 800 600 400 200	13 11 9 7 4 2	88 90 93 95 100 104		1000 800 600 400 200	13 9 7 5 2	79 81 83 88 91

3.5 DIRECT DIFFUSED (DD3)	LUMEN/FT	WATT/FT	LPW	3.5 DIRECT DIFFUSED (DD3) REGRESSED	LUMEN/FT	WATT/FT	LPW
	1400 1200 1000 800 600 400 200	13 11 8 7 5 3 2	110 114 116 119 123 127 129		1200 1000 800 600 400 200	13 11 8 7 4 2	95 98 100 103 107 114

INDIRECT BATWING (UD1)	LUMEN/FT	WATT/FT	LPW	INDIRECT ASYMMETRIC (UD3)	LUMEN/FT	WATT/FT	LPW
	1200	11	116		1000	11	82
	1000	9	119		800	9	84
	800	7	122		600	7	89
	600	5	130		400	4	91
	400	3	137		200	2	95
	200	1	144				

INDIRECT OPAL DIFFUSER (UD2)	LUMEN/FT	WATT/FT	LPW
	1000	11	98
	800	9	100
	600	6	106
	400	3	112
	200	2	113