Project Name:	Fixture Type:
Fixture Code:	Quantities:



GENERAL SPECIFICATION

Body and trim

Steel and aluminum.

Diffuser

Opal acrylic.

Drivers

HPF electronic, 120-277V (EU-240V), 0-10V, 1% dimming standard.

Delivered Lumens

Delivered lumens & LPW based on 3000K (min 80 CRI).

MOUNTING & OPTICS



Wall Front/Back

Finish

Back plate, powder coated gloss white. Cover, finished as listed.

Dust covers

Opal dust cover standard.

Mechanical

Luminaires mount directly to a junction box. (by others - North America Only).

HOW TO ORDER

A. LUMINAIRE

591110 591110 **591141** 591141

B. CCT

30 3000K (min 80 CRI) 35 3500K (min 80 CRI) 40 4000K (min 80 CRI)

C. DIFFUSER

OP Opal FB Beige faux alabaster FW White faux alabaster

D. FINISH

MB Metallic Bronze MS Silver Metallic **AB** Antique Brass **PB** Polished Brass

SB Satin Brass **SN** Satin Nickel OT Other painted finish (RAL number F40 Other Non-RAL painted finish required) (sample chip required)

OT & BL1 have a one time set-up charge regardless of quantity.

TECHNICAL DATA

LUMINAIRE

Code	591110	591141
Power (LED)	14W	32W
Delivered Ims	940	2120
LPW	64	69
Height (A)	13"	24"
Width (B)	8.5"	10"
Weight	9lb	18lb

APPROVALS











DIMENSIONAL DIAGRAMS

