

XACARA SM™ - WALL SURFACE

Project Name:	Fixture Type:
Fixture Code:	Quantities:




XACARA SM™ - WALL SURFACE

GENERAL SPECIFICATION

Body and trim	Array housings
Steel and aluminium (extruded).	Die cast aluminium.
Gimbal	Reflectors
Fully articulating on two axes.	Medium and wide beam. Highly reflective, specular finish, vacuum plated.
Protective lens	Mounting
Clear glass.	Mounts directly over a 2"x3" switch box (by others).
Orientation	Visible cable
Ceiling or wall. May be inverted.	Silver.
Finish	Drivers
Powder coated, as specified.	HPF electronic for 120-277V (EU-240V). 0-10V dimming.
L70 @25°C (77°F)	Delivered Lumens
> 60,000 hrs.	Delivered lumens & LPW based on 3000K (min 80 CRI).

MOUNTING & OPTICS



Wall

XACARA SM™ - WALL SURFACE

HOW TO ORDER

A. LUMINAIRE

502210 502210	502215 502215	502220 502220	502230 502230
502240 502240			

B. CCT/CRI

30A 3000K (min 80 CRI)	30B 3000K (min 90 CRI)	35A 3500K (min 80 CRI)	35B 3500K (min 90 CRI)
40A 4000K (min 80 CRI)	40B 4000K (min 90 CRI)		

C. REFLECTORS

ME Medium 36°	XW Extra wide 70°
----------------------	--------------------------

D. FINISH

BL Black	MS Silver Metallic	WH White
-----------------	---------------------------	-----------------

TECHNICAL DATA

LUMINAIRE

Code	502210	502215	502220	502230	502240
Power (LED)	1 x 26W	1 x 26W	2 x 26W	3 x 26W	4 x 26W
Delivered lms	1 x 2085	1 x 2085	2 x 2085	3 x 2085	4 x 2085
LPW	80	80	80	80	80

APPROVALS



XACARA SM™ - WALL SURFACE

DIMENSIONAL DIAGRAMS

