

# TRILOGY CRADLE™ - CEILING SURFACE

Project Name:	Fixture Type:
Fixture Code:	Quantities:



# TRILOGY CRADLE™ - CEILING SURFACE

## GENERAL SPECIFICATION

**Body and trim**

Steel and aluminum.

**Finish**

Back plate, powder coated gloss white. Trim, painted or plated as listed.

**Diffuser**

Three ply satin opal glass.

**Drivers**

HPF electronic, 120/277V (EU-240V). 0-10V, 1% dimming standard.

**Luminaire orientation**

Ceiling or wall mounted.

**Mechanical**

Mounts directly to a junction box (by others - North America only).

**Delivered Lumens**

Delivered lumens & LPW based on 3000K (min 80 CRI).

**Approvals**

Damp Location (Indoor use only).

## MOUNTING & OPTICS



Ceiling Direct/Indirect

# TRILOGY CRADLE™ - CEILING SURFACE

## HOW TO ORDER

### A. LUMINAIRE

**638818** 63 8818

### B. CCT

**30** 3000K (min 80 CRI)

**35** 3500K (min 80 CRI)

**40** 4000K (min 80 CRI)

### C. FINISH

**WH** White

**MB** Metallic Bronze

**MS** Silver Metallic

**PC** Polished Chrome

**SC** Satin Chrome

**SN** Satin Nickel

**OT** Other painted finish (RAL number required)

**F40** Other Non-RAL painted finish (sample chip required)

OT & BL1 have a one time set-up charge regardless of quantity.

## TECHNICAL DATA

### LUMINAIRE

Code	<b>638818</b>
Power (LED)	21W
Delivered lms	1240
LPW	59
Weight	6.3Kg/14lb

## APPROVALS



# TRILOGY CRADLE™ - CEILING SURFACE

## DIMENSIONAL DIAGRAMS

