

TRILOGY HALO™ - CEILING SURFACE

Project Name:	Fixture Type:
Fixture Code:	Quantities:



TRILOGY HALO™ - CEILING SURFACE

GENERAL SPECIFICATION

Body and trim

Steel and aluminum.

Diffuser

Three ply satin opal glass.

Luminaire orientation

Ceiling or wall mounted.

Delivered Lumens

Delivered lumens & LPW based on 3000K (min 80 CRI).

Finish

Back plate, powder coated gloss white. Trim, painted or plated as listed.

Drivers

HPF electronic, 120/277V (EU-240V). 0-10V, 1% dimming standard.

Mechanical

Mounts directly to a junction box (by others - North America only).

Approvals

Damp Location (Indoor use only).

MOUNTING & OPTICS



Ceiling Direct/Indirect



Direct-indirect

TRILOGY HALO™ - CEILING SURFACE

HOW TO ORDER

A. LUMINAIRE

638860 21W, 1240 lms

B. CCT

30 3000K (min 80 CRI) **35** 3500K (min 80 CRI) **40** 4000K (min 80 CRI)

C. FINISH

WH White	BM Bronze Metallic Textured	MS Silver Metallic	PC Polished Chrome
SC Satin Chrome	SN Satin Nickel	F39 Other painted finish (RAL number required)	F40 Other Non-RAL painted finish (sample chip required)

F39 & F40 have a one time set-up charge regardless of quantity.

TECHNICAL DATA

LUMINAIRE

Code	638860
Power (LED)	21W
Delivered lms	1240
LPW	59
Weight	14lb

APPROVALS



TRILOGY HALO™ - CEILING SURFACE

DIMENSIONAL DIAGRAMS

