

TRILOGY™ - SUSPENDED

Project Name:	Fixture Type:
Fixture Code:	Quantities:



TRILOGY™ - SUSPENDED

GENERAL SPECIFICATION

Body and trim

Aluminium and steel.

Finish

Gear tray, powder coated gloss white. Trim, powder coated or plated as listed.

Drivers

HPF electronic, 120/277V (EU-240V). 0-10V, 1% dimming standard.

Suspension

Three cables.

Diffusers

Hand blown, triple ply, satin opal glass.

Delivered Lumens

Delivered lumens & LPW based on 3000K (min 80 CRI).

MOUNTING & OPTICS



Suspended Direct/Indirect

TRILOGY™ - SUSPENDED

HOW TO ORDER

A. LUMINAIRE

639810 639810

B. CCT

30 3000K (min 80 CRI) **35** 3500K (min 80 CRI) **40** 4000K (min 80 CRI)

C. FINISH

MS Silver Metallic	PC Polished Chrome	SC Satin Chrome	SN Satin Nickel
OT Other painted finish (RAL number required)	F40 Other Non-RAL painted finish (sample chip required)		

OT & BL1 have a one time set-up charge regardless of quantity.

D. OPTIONS

HR Halo Rings **CB** Cradle Bars

TECHNICAL DATA

LUMINAIRE

Code	639810
Power (LED)	21W LED
Delivered lms	1240
LPW	59

APPROVALS



TRILOGY™ - SUSPENDED

DIMENSIONAL DIAGRAMS

