

# ZEDOS PM™ - WALL OR CEILING SURFACE

Project Name:	Fixture Type:
Fixture Code:	Quantities:



# ZEDOS PM™ - WALL OR CEILING SURFACE

## GENERAL SPECIFICATION

**Body and trim**

Steel and aluminum.

**Finish**

Powder coated or plated as listed.

**Diffusers**

Opal polycarbonate.

**Drivers**

HPF electronic, 120-277V (EU-240V). 0-10V, 1% dimming standard.

**Luminaire orientation**

Ceiling or wall.

**Mechanical**

Mounts directly to a junction box (by others - North America only).

**Delivered Lumens**

Delivered lumens & LPW based on 3000K (min 80 CRI).

**Approvals**

Damp Location (Indoor use only).

## MOUNTING & OPTICS



Ceiling

# ZEDOS PM™ - WALL OR CEILING SURFACE

## HOW TO ORDER

### A. LUMINAIRE

<b>681680</b> 681680	<b>682180</b> 682180	<b>682183</b> 682183	
<b>B. CCT</b>			
<b>30</b> 3000K (min 80 CRI)	<b>35</b> 3500K (min 80 CRI)	<b>40</b> 4000K (min 80 CRI)	
<b>C. FINISH</b>			
<b>WH</b> White	<b>MS</b> Silver Metallic	<b>SN</b> Satin Nickel	<b>OT</b> Other painted finish (RAL number required)
<b>F40</b> Other Non-RAL painted finish (sample chip required)			

OT & BL1 have a one time set-up charge regardless of quantity.

## TECHNICAL DATA

### LUMINAIRE

Code	<b>681680</b>	<b>682180</b>	<b>682183</b>
Power (LED)	28W	28W	36W
Delivered lms	1894	2002	2638
LPW	68	71	73
Diameter (A)	15.7"	20.8"	20.8"
Depth (D)	4"	4"	4"
Weight	4lb	5.5lb	5.5lb

## APPROVALS



# ZEDOS PM™ - WALL OR CEILING SURFACE

## DIMENSIONAL DIAGRAMS

