

ZEDOS™ - CEILING SURFACE

Project Name:	Fixture Type:
Fixture Code:	Quantities:



ZEDOS™ - CEILING SURFACE

GENERAL SPECIFICATION

Body and trim

Steel and aluminum.

Diffusers

Opal polycarbonate.

Luminaire orientation

Ceiling or wall.

Delivered Lumens

Delivered lumens & LPW based on 3000K (min 80 CRI).

Finish

Powder coated or plated as listed.

Drivers

HPF electronic, 120-277V (EU-240V). 0-10V, 1% dimming standard.


Mechanical

Mounts directly to a junction box (by others - North America only).

Approvals

Damp Location (Indoor use only).

MOUNTING & OPTICS



ZEDOS™ - CEILING SURFACE

HOW TO ORDER

A. LUMINAIRE

681670 15.7", 28W, 1793 lms	682170 20.8", 28W, 1949 lms	682173 20.8", 36W, 2568 lms	
B. CCT			
30 3000K (min 80 CRI)	35 3500K (min 80 CRI)	40 4000K (min 80 CRI)	
C. FINISH			
WH White	MS Silver Metallic	SN Satin Nickel	F39 Other painted finish (RAL number required)
F40 Other Non-RAL painted finish (sample chip required)			

F39 & F40 have a one time set-up charge regardless of quantity.

TECHNICAL DATA

LUMINAIRE

Code	681670	682170	682173
Power (LED)	28W	28W	36W
Delivered lms	1793	1949	2568
LPW	64	70	72
Diameter (A)	15.7"	20.8"	20.8"
Depth (D)	4"	4"	4"
Weight	4lb	5.5lb	5.5lb

APPROVALS



ZEDOS™ - CEILING SURFACE

DIMENSIONAL DIAGRAMS

