

# MASSIO™ - WALL SURFACE EXTERIOR

|               |               |
|---------------|---------------|
| Project Name: | Fixture Type: |
| Fixture Code: | Quantities:   |



# MASSIO™ - WALL SURFACE EXTERIOR

## GENERAL SPECIFICATION

### Body and trim

Low copper, die-cast aluminum highly resistant to oxidation.

### Gasket

Silicone.

### External screws

A4 stainless steel treated with highly antioxidant water-repellent lubricating solution to ensure easy opening.

### Drivers

HPF, electronic for 120V/277V.

### Delivered Lumens

Delivered lumens & LPW based on 3000K (min 80 CRI).

### Diffuser

3mm/0.12" tempered glass/convex lens.

### Finish

Powder coated.

### Cable entry

M20 gland for DIA 8-12mm/0.2-0.47" cables.

### Mechanical

For surface mounting.

## MOUNTING & OPTICS



Ext-Wall Downlight    Ext-Wall Up/Down

# MASSIO™ - WALL SURFACE EXTERIOR

## HOW TO ORDER

### A. LUMINAIRE

|                        |                        |                        |                        |
|------------------------|------------------------|------------------------|------------------------|
| <b>8308140</b> 8308140 | <b>8308130</b> 8308130 | <b>8308132</b> 8308132 | <b>8308138</b> 8308138 |
| <b>8308134</b> 8308134 | <b>8308136</b> 8308136 |                        |                        |

### B. CCT

|                              |                              |
|------------------------------|------------------------------|
| <b>30</b> 3000K (min 80 CRI) | <b>40</b> 4000K (min 80 CRI) |
|------------------------------|------------------------------|

### C. FINISH

|                 |                           |                         |
|-----------------|---------------------------|-------------------------|
| <b>BL</b> Black | <b>AG</b> Anthracite Gray | <b>GR</b> Gray RAL 9006 |
|-----------------|---------------------------|-------------------------|

### D. DIMMING

|                              |
|------------------------------|
| <b>DB</b> Dimming 0-10V, 10% |
|------------------------------|

Dimming not available for 830 8140

## TECHNICAL DATA

### LUMINAIRE

| Code          | 8308140                         | 8308130         | 8308132                   | 8308138                             | 8308134        | 8308136            |
|---------------|---------------------------------|-----------------|---------------------------|-------------------------------------|----------------|--------------------|
| Power (LED)   | 6W                              | 26W             | 26W                       | 16W                                 | 26W            | 6W+18W             |
| Distibution   | 2° x 35°<br>Asymmetrical Narrow | 32° Medium Down | 2 x 32° Medium<br>Up/Down | 4 x (2°x35°)<br>Asymmetrical Narrow | 4 x 32° Medium | Spot Up/Flood Down |
| Delivered lms | 31                              | 361             | 898                       | 118                                 | 449            | ---                |

## APPROVALS



MASSIO™ - WALL SURFACE EXTERIOR

DIMENSIONAL DIAGRAMS

