

PEYOTE™ - WALL SURFACE EXTERIOR

Project Name:	Fixture Type:
Fixture Code:	Quantities:



PEYOTE™ - WALL SURFACE EXTERIOR

GENERAL SPECIFICATION

Housing

Die-cast and extruded aluminium.

Lens

Clear glass.

Finish

Silver powder coated light gray or black coated as standard. *(For custom finishes please contact factory).*

Minimum Starting Temperature

-30°C.

Delivered Lumens

Delivered lumens & LPW based on 3000K (min 80 CRI).

External Screws

Stainless steel.

Gaskets

One piece silicone.

Drivers

HPF, electronic for 120-277V (EU-240V).

Weight

Maximum 8.8lb.

MOUNTING & OPTICS



Ext-Wall Downlight Ext-Wall Up/Down

PEYOTE™ - WALL SURFACE EXTERIOR

HOW TO ORDER

A. LUMINAIRE

8309000 360°, 933 lms **8309010** 180°, 466 lms **8309020** 2 x 90°, 466 lms

B. CCT

30 3000K (min 80 CRI) **40** 4000K (min 80 CRI)

C. FINISH

BL Black **GR** Light Gray

D. OPTIONS

8309099 Anchorage Base for poured concrete

TECHNICAL DATA

LUMINAIRE

Code	8309000	8309010	8309020
Power (LED)	14W	14W	14W
Delivered lms	933	466	466
LPW	67	33	33
Distibution	360°	180°	2 x 90°





APPROVALS



PEYOTE™ - WALL SURFACE EXTERIOR

DIMENSIONAL DIAGRAMS

143mm/5.6" DIA



160mm/6.3" DIA