

# SPIA™ - WALL RECESSED EXTERIOR

|               |               |
|---------------|---------------|
| Project Name: | Fixture Type: |
| Fixture Code: | Quantities:   |

# SPIA™ - WALL RECESSED EXTERIOR

## GENERAL SPECIFICATION

### Housing

Low copper, die-cast aluminum highly resistant to oxidation.

### Gasket

Silicone.

### Reflectors

High purity aluminum.

### Cable entry

Type A, M16 gland for DIA 5-10mm/0.22-0.4" cables. Type B, Double silicon cable gland for DIA 10-14mm/0.4-0.5" cables.

### Rough-in housing

Thermoplastic.

### Diffuser

5mm/0.2" tempered glass.

### Finish

Powder coated.

### External screws

A4 stainless steel treated with highly antioxidant water-repellent lubricating solution to ensure easy opening.


### Drivers

HPF, electronic 120-277V.

### Mechanical

For wall installation in poured concrete/brick.

## MOUNTING & OPTICS



Ext-Wall Recessed

# SPIA™ - WALL RECESSED EXTERIOR

## HOW TO ORDER

### A. LUMINAIRE

|                        |                        |                        |                        |
|------------------------|------------------------|------------------------|------------------------|
| <b>8207410</b> 8207410 | <b>8207412</b> 8207412 | <b>8207414</b> 8207414 | <b>8207416</b> 8207416 |
|------------------------|------------------------|------------------------|------------------------|

### B. CCT

|                              |                              |
|------------------------------|------------------------------|
| <b>30</b> 3000K (min 80 CRI) | <b>40</b> 4000K (min 80 CRI) |
|------------------------------|------------------------------|

### C. FINISH

|                 |                           |                      |
|-----------------|---------------------------|----------------------|
| <b>BL</b> Black | <b>AG</b> Anthracite Gray | <b>GR</b> Light Gray |
|-----------------|---------------------------|----------------------|

### D. OPTIONS

|                                              |                                                          |                              |
|----------------------------------------------|----------------------------------------------------------|------------------------------|
| <b>DB</b> Dimming (Trailing Edge, 120V only) | <b>TF</b> Turtle Friendly Amber LEDs (0.35 of 3000K lms) | <b>SC</b> Second Cable Entry |
|----------------------------------------------|----------------------------------------------------------|------------------------------|

### E. ROUGH-IN HOUSING (REQUIRED)

|                                               |                                               |
|-----------------------------------------------|-----------------------------------------------|
| <b>RIH5297</b> Rough-In Housing (Types A & B) | <b>RIH5301</b> Rough-In Housing (Types C & D) |
|-----------------------------------------------|-----------------------------------------------|

# SPIA™ - WALL RECESSED EXTERIOR

## TECHNICAL DATA

### LUMINAIRE

|                |                |                |                |                |
|----------------|----------------|----------------|----------------|----------------|
| Code           | 8207410        | 8207412        | 8207414        | 8207416        |
| Power          | 1W Half Louver | 1W Full Louver | 3W Half Louver | 3W Full Louver |
| Initial Lumens | 75lm           | 75lm           | 225lm          | 225lm          |
| Dimensions     | Type A         | Type B         | Type C         | Type D         |

## APPROVALS



SPIA™ - WALL RECESSED EXTERIOR

DIMENSIONAL DIAGRAMS

