

CRISTAL SML™ - INGROUND EXTERIOR

Project Name:	Fixture Type:
Fixture Code:	Quantities:

CRISTAL SML™ - INGROUND EXTERIOR

GENERAL SPECIFICATION

Housing Die-cast aluminum. Walk over 1000Kg/2200lbs.	External Screws Stainless steel.
Lens 6mm/0.25" sandblasted glass with clear windows for LEDs.	Gaskets One piece silicone.
Drivers HPF, electronic for 120-277V (EU-240V).	Minimum Starting Temperature -30°C.
Conduit entry PG11 gland for 11mm/0.625" DIA cable.	Recessed housing Molded polypropylene, gray, with stainless mounting trim. Specify as a separate line item.
Delivered Lumens Delivered lumens and LPW based on 3000K (min 80 CRI).	

MOUNTING & OPTICS



Ext-Inground

CRISTAL SML™ - INGROUND EXTERIOR

HOW TO ORDER

A. LUMINAIRE

810108 810108	810109 810109	810107 810107
----------------------	----------------------	----------------------

B. CCT

30 3000K (min 80 CRI)	40 4000K (min 80 CRI)
------------------------------	------------------------------

C. RECESSED HOUSING (REQUIRED)

810900 Recessed Housing for Wall Installation	810901 Recessed Housing for Inground Installation
--	--

TECHNICAL DATA

LUMINAIRE

Code	810108	810109	810107
Power	7W	7W	7W
Type	Glass Only	Glass Only	Glass Only
Distribution	Wall	Inground 10°	Inground 36°
Delivered lms	396	466	466

APPROVALS



CRISTAL SML™ - INGROUND EXTERIOR

DIMENSIONAL DIAGRAMS

