

CUBO CL™ - CEILING & CANOPY EXTERIOR

Project Name:	Fixture Type:
Fixture Code:	Quantities:



CUBO CL™ - CEILING & CANOPY EXTERIOR

GENERAL SPECIFICATION

Housing Die-cast aluminum.	External Screws Stainless steel.
Lens 6mm/0.25" tempered glass.	Gaskets One piece silicone.
Finish Silver powder coated RAL9006 or black powder coated.	Drivers HPF, electronic for 120-277V (EU-240V).
Minimum Starting Temperature -30°C for LEDs.	Conduit entry PG11 gland for 11mm/0.625" DIA cable.
Delivered Lumens Delivered lumens and LPW based on 3000K (min 80 CRI).	

MOUNTING & OPTICS



Ext-Ceiling/Canopy

CUBO CL™ - CEILING & CANOPY EXTERIOR

HOW TO ORDER

A. L

810347 810347 **810348** 810348

B. CCT

30 3000K (min 80 CRI) **40** 4000K (min 80 CRI)

C. FINISH

BL Black **GR** Gray RAL 9006

D. DIMMING

DB Dimming (0-10V, 10%)

TECHNICAL DATA

LUMINAIRE

Code	810347	810348
Power (LED)	14W	14W
Beam	8°	40°
Delivered lms	1049	1049

APPROVALS



CUBO CL™ - CEILING & CANOPY EXTERIOR

DIMENSIONAL DIAGRAMS

