

# ERELLA™ - SUSPENDED

Project Name:	Fixture Type:
Fixture Code:	Quantities:



# ERELLA™ - SUSPENDED

## GENERAL SPECIFICATION

### Body and trim

Steel and aluminum.

### Finish

Gear tray, powder coated gloss white. Trim, powder coated or plated as listed.

### Dust covers

Clear polycarbonate.

### Mechanical

Luminaires mount directly over a junction box (by others - North America only).

### L70 @25°C (77°F)

> 50,000 hrs.

### Suspension

Single tube with three support cables.

### Diffusers

Acrylic.

### Drivers

HPF electronic, 120/277V (EU-240V). 0-10V, 1% dimming standard.

### Remote Emergency

Emergency option provides a 1.5 hour (3 hours for EU) emergency lighting facility.

The remote system includes the inverter module, NiCad batteries and a remote wall/ceiling LED charge indicator and test switch (NA only) Maximum distance between wall/ceiling plate and luminaire is 4.5m/15'. Test switch fits a single gang box (not supplied).

## MOUNTING & OPTICS



Suspended Direct/Indirect



Direct-indirect

# ERELLA™ - SUSPENDED

## HOW TO ORDER

### A. LUMINAIRE

<b>127010</b> 23", 12714 lms	<b>127020</b> 29", 15439 lms	<b>127030</b> 33", 19334 lms	<b>127040</b> 46", 30973 lms
<b>127050</b> 56", 38150 lms			

### B. CCT

<b>30</b> 3000K (min 80 CRI)	<b>35</b> 3500K (min 80 CRI)	<b>40</b> 4000K (min 80 CRI)	
------------------------------	------------------------------	------------------------------	--

### C. FINISH

<b>WH</b> White	<b>BM</b> Bronze Metallic Textured	<b>MS</b> Silver Metallic	<b>AB</b> Antique Brass
<b>PB</b> Polished Brass	<b>SB</b> Satin Brass	<b>PC</b> Polished Chrome	<b>SN</b> Satin Nickel
<b>F39</b> Other painted finish (RAL number required)	<b>F40</b> Other Non-RAL painted finish (sample chip required)		

F39 & F40 have a one time set-up charge regardless of quantity.

### D. DIFFUSER

<b>OP</b> Opal			
----------------	--	--	--

### E. DIMMING

<b>DA</b> DALI Drivers	<b>DX</b> DMX Drivers		
------------------------	-----------------------	--	--

### F. OPTIONS

<b>RE</b> Remote Emergency (max distance 10ft, 120/277V)	<b>CB</b> Cradle Bars	<b>SW</b> Swivel Canopy (42 Degrees)	
----------------------------------------------------------	-----------------------	--------------------------------------	--

### G. SUSPENSION LENGTHS

<b>S1</b> 6" additional suspension length	<b>S2</b> 12" additional suspension length	<b>S3</b> 18" additional suspension length	<b>S4</b> 24" additional suspension length
-------------------------------------------	--------------------------------------------	--------------------------------------------	--------------------------------------------

# ERELLA™ - SUSPENDED

## TECHNICAL DATA

### LUMINAIRE

Code	127010	127020	127030	127040	127050
Power (LED)	128W	149W	170W	283W	350W
Delivered lms	12714	15439	19334	30973	38150
LPW	100	104	114	109	109
Diameter (A)	23"	29"	33"	46"	56"
Depth (D)	7"	9"	9"	12"	18"
Height (H)	17.5"	23"	23"	23"	29.5"

## APPROVALS



ERELLA™ - SUSPENDED

DIMENSIONAL DIAGRAMS

