

ZEDOS PM™ - SUSPENDED

Project Name:	Fixture Type:
Fixture Code:	Quantities:



ZEDOS PM™ - SUSPENDED

GENERAL SPECIFICATION

Body and trim

Steel and aluminium.

Finish

Gear tray, powder coated gloss white. Trim, powder coated or plated as listed.

Dust covers

Clear polycarbonate.

Remote Emergency

Emergency option provides a 1.5 hour (3 hours for EU) emergency lighting facility. The remote system includes the inverter module, NiCad batteries and a remote wall/ceiling LED charge indicator and test switch (NA only) Maximum distance between wall/ceiling plate and luminaire is 4.5m/15'. Test switch fits a single gang box (not supplied).

Delivered Lumens

Delivered lumens & LPW based on 3000K (min 80 CRI).

Suspension

Single tube with four decorative tubes.

Diffusers

Acrylic.

Drivers

HPF electronic, 120/277V (EU-240V), 0-10V, 1% dimming standard.

L70 @25°C (77°F)

> 50,000 hrs.

MOUNTING & OPTICS



Suspended Direct/Indirect

ZEDOS PM™ - SUSPENDED

HOW TO ORDER

A. LUMINAIRE

687110 687110	687120 687120	687130 687130
----------------------	----------------------	----------------------

B. CCT

30 3000K (min 80 CRI)	35 3500K (min 80 CRI)	40 4000K (min 80 CRI)
------------------------------	------------------------------	------------------------------

C. FINISH

WH White	MB Metallic Bronze	MS Silver Metallic	PC Polished Chrome
SB Satin Brass	SC Satin Chrome	SN Satin Nickel	OT Other painted finish (RAL number required)
F40 Other Non-RAL painted finish (sample chip required)			

OT & BL1 have a one time set-up charge regardless of quantity.

D. DIFFUSER

OP Opal

E. DIMMING

DA DALI Drivers	DX DMX Drivers
------------------------	-----------------------

F. OPTIONS

RE Remote Emergency (max distance 10 ft, 120/277V)	CB Cradle Bars	SW Swivel Canopy (42 degrees)
---	-----------------------	--------------------------------------

G. SUSPENSION LENGTH

S1 6" Additional Suspension Length	S2 12" Additional Suspension Length	S3 18" Additional Suspension Length	S4 24" Additional Suspension Length
---	--	--	--

ZEDOS PM™ - SUSPENDED

TECHNICAL DATA

LUMINAIRE

Code	687110	687120	687130
Power (LED)	150W	211W	282W
Delivered lms	15439	22631	30043
LPW	103	107	107
Diameter (A)	29"	37"	47"
Diameter (B)	5.7"	5.7"	7.9"
Depth (D)	6.5"	7"	9"
Height (H)	24"	24"	29.5"
Height (A)	1"	1"	1.75"

APPROVALS



ZEDOS PM™ - SUSPENDED

DIMENSIONAL DIAGRAMS

