

TRILOGY™ - CEILING SURFACE

Project Name:	Fixture Type:
Fixture Code:	Quantities:



TRILOGY™ - CEILING SURFACE

GENERAL SPECIFICATION

Body and trim

Steel and aluminum.

Finish

Back plate, powder coated gloss white.

Diffuser

Three ply satin opal glass.

Drivers

HPF electronic, 120/277V (EU-240V). 0-10V, 1% dimming standard.

Luminaire orientation

Ceiling or wall mounted.

Mechanical

Mounts directly to a junction box (by others - North America only).

Delivered Lumens

Delivered lumens & LPW based on 3000K (min 80 CRI).


Approvals

Damp Location (Indoor use only).

MOUNTING & OPTICS



Ceiling Direct/Indirect



Direct-indirect

TRILOGY™ - CEILING SURFACE

HOW TO ORDER

A. LUMINAIRE

635220 21W, 1240 lms

B. CCT

30 3000K (min 80 CRI) **35** 3500K (min 80 CRI) **40** 4000K (min 80 CRI)

TECHNICAL DATA

LUMINAIRE

Code	635220
Power (LED)	21W
Delivered lms	1240
LPW	59
Weight	14lb

APPROVALS



TRILOGY™ - CEILING SURFACE

DIMENSIONAL DIAGRAMS

