

LPU SQ™ - SUSPENDED

Project Name:	Fixture Type:
Fixture Code:	Quantities:

LPU SQ™ - SUSPENDED

GENERAL SPECIFICATION

Body and trim

Extruded aluminum and steel.

Finish

Powder coated as specified.

Power cable

Silver braided.

Mechanical

Luminaire mounts directly over a junction box.

L70 @25°C (77°F)

> 50,000 hrs.

Suspension

Four cables.

Dust cover

Clear polycarbonate.

Drivers

HPF, electronic, 0-10V (EU-240V), 10% dimming standard.

Remote emergency system

Emergency option provides a 1.5 hour emergency lighting facility. The remote system includes the inverter module, NiCad batteries and a remote wall/ceiling LED charge indicator and test switch (maximum distance between wall/ceiling plate and luminaire is 4.5m/15'). Test switch fits a single gang box (not supplied).

MOUNTING & OPTICS



Suspended Direct

LPU SQ™ - SUSPENDED

HOW TO ORDER

A. LUMINAIRE

773501 77 3501 **773511** 77 3511

B. CCT

30 3000K (min 80 CRI) **35** 3500K (min 80 CRI) **40** 4000K (min 80 CRI)

C. FINISH

WH White **MS** Silver Metallic **OT** Other Painted Finish (RAL number required)

D. DIMMING

DA DALI Drivers **DX** DMX Drivers

E. OPTIONS

RE Remote Emergency (max distance 10 ft)

LPU SQ™ - SUSPENDED

TECHNICAL DATA

LUMINAIRE

Code	773501	773511
Power (LED)	108W	226W
Delivered lms	13761	28365
LPW	127	126
Width (A)	32" SQ	32" SQ

APPROVALS



LPU SQ™ - SUSPENDED

DIMENSIONAL DIAGRAMS

