

# XACARA RD™ - SUSPENDED

|               |               |
|---------------|---------------|
| Project Name: | Fixture Type: |
| Fixture Code: | Quantities:   |



# XACARA RD™ - SUSPENDED

## GENERAL SPECIFICATION

### Body and trim

Steel and aluminium.

### Gimbal

Fully articulating on two axes.

### Reflectors

Medium and wide beam. Highly reflective, specular finish, vacuum plated.

### Power cable

Silver braided.

### Drivers

HPF electronic for 120-277V (EU-240V). 0-10V dimming (10%).

### Delivered Lumens

Delivered lumens & LPW based on 3000K (min 80 CRI).

### Note

*Photometric testing performed using LM79 procedures.*

### Array housings

Die cast aluminium.

### Suspension

Three cables, fully adjustable.

### Protective lens

Clear glass.

### Finish

Powder coated, as specified.

### L70 @25°C (77°F)

> 60,000 hrs.

### Approvals

Damp Location (Indoor use only).

## MOUNTING & OPTICS



Suspended Direct

36°

70°



# XACARA RD™ - SUSPENDED

## HOW TO ORDER

### A. LUMINAIRE

**501030** 50 1030                      **501060** 50 1060

### B. CCT/CRI

|                               |                               |                               |                               |
|-------------------------------|-------------------------------|-------------------------------|-------------------------------|
| <b>30A</b> 3000K (min 80 CRI) | <b>30B</b> 3000K (min 90 CRI) | <b>35A</b> 3500K (min 80 CRI) | <b>35B</b> 3500K (min 90 CRI) |
| <b>40A</b> 4000K (min 80 CRI) | <b>40B</b> 4000K (min 90 CRI) |                               |                               |

### C. REFLECTOR

**ME** Medium 36°                      **XW** Extra Wide 70°

### D. FINISH

**BL** Black                      **MS** Silver Metallic                      **WH** White

## TECHNICAL DATA

### LUMINAIRE

|               |          |          |
|---------------|----------|----------|
| Code          | 501030   | 501060   |
| Power (LED)   | 3 x 26W  | 6 x 26W  |
| Delivered lms | 3 x 2085 | 6 x 2085 |
| LPW           | 80       | 80       |

## APPROVALS



XACARA RD™ - SUSPENDED

DIMENSIONAL DIAGRAMS

