

XACARA SQ™ - SUSPENDED

Project Name:	Fixture Type:
Fixture Code:	Quantities:



XACARA SQ™ - SUSPENDED



XACARA SQ™ - SUSPENDED

GENERAL SPECIFICATION

Body and trim

Steel and aluminium.

Array housings

Die cast aluminium.

Gimbal

Fully articulating on two axes.

Suspension

Two or four cables, fully adjustable.

Reflectors

Highly reflective, specular finish, vacuum plated.

Protective lens

Clear glass.

Power cable

Silver braided.

Finish

Powder coated, as specified.

Drivers

HPF electronic for 120-277V (EU-240V). 0-10V dimming (10%).

L70 @25°C (77°F)

> 60,000 hrs.

Delivered Lumens

Delivered lumens & LPW based on 3000K (min 80 CRI).


Approvals

Damp Location (Indoor use only).

Note

Photometric testing performed using LM79 procedures.

MOUNTING & OPTICS



Suspended Direct

XACARA SQ™ - SUSPENDED

HOW TO ORDER

A. LUMINAIRE

501250 501250 **501260** 501260

B. CCT/CRI

30A 3000K (min 80 CRI)	30B 3000K (min 90 CRI)	35A 3500K (min 80 CRI)	35B 3500K (min 90 CRI)
40A 4000K (min 80 CRI)	40B 4000K (min 90 CRI)		

C. REFLECTOR

ME Medium 36° **XW** Extra Wide 70°

D. FINISH

BL Black **MS** Silver Metallic **WH** White

TECHNICAL DATA

LUMINAIRE

Code	501250	501260
Power (LED)	2 x 26W	4 x 26W
Delivered lms	2 x 2085	4 x 2085
LPW	80	80
CBCP	4104	4104

APPROVALS



XACARA SQ™ - SUSPENDED

DIMENSIONAL DIAGRAMS

