

GENERAL SPECIFICATION

Housing: Die-cast aluminum. Walk over 1000Kg/2200lbs.

External Screws: Stainless steel.

Lens: 6mm/0.25" sandblasted glass with clear windows for LEDs.

Gaskets: One piece silicone.

Drivers: HPF, electronic for 120-277V (EU-240V). 0-10V dimming 120-277V.

Minimum Starting Temperature: -30°C.

Conduit entry: PG11 gland for 11mm/0.625" DIA cable.


Recessed housing: Molded polypropylene, gray, with stainless mounting trim. Specify as a separate line item.

Delivered Lumens: Delivered lumens and LPW based on 3000K (min 80 CRI).


MOUNTING & OPTICS




Ext-Inground



81 0127-16W-36 DEG



81 0128-16W-WALL



81 0129-16W-10 DEG

HOW TO ORDER

A SPECIFY LUMINAIRE

Code	Power	Type	Distribution	Delivered lms
81 0128	16W	Glass Only	Wall	892
81 0129	16W	Glass Only	Inground 10°	1049
81 0127	16W	Glass Only	Inground 36°	1049

B SPECIFY CCT

30	3000K (min 80 CRI)
40	4000K (min 80 CRI)

C SPECIFY RECESSED HOUSING (REQUIRED)


81 0902	Recessed Housing for Wall Installation
81 0903	Recessed Housing for Inground Installation

EXAMPLE CODE



810128/30 + 810902

DIMENSIONAL DIAGRAMS



160mm/6.3" DIA



147mm/5.8" DIA




SS Bezel




Glass only

110mm/4.3"



Wall



Inground

APPROVALS



IP67