



## GENERAL SPECIFICATION

**Housing:** Die-Formed steel.

**Horizontal bars:** Die-cast zinc.

**Perforated accents:** Steel, finished as specified.

**Finish:** Powder coated paint or plated.

**Front diffuser:** UV stabilized polycarbonate with vertical ribs.

**Rear side (halo) diffuser:** Extruded opal acrylic.

**Upper and lower dust covers:** Opal polycarbonate.


**Drivers:** HPF electronic, 120-277V (EU-240V). 0-10V, 1% dimming standard.

**Mechanical:** Mounts directly to a standard electrical junction box (by others - North America only). Additional mounting points provided.

Mounting hardware (by others).

**Delivered Lumens:** Delivered lumens & LPW based on 3000K (min 80 CRI).

## MOUNTING & OPTICS



Wall Direct

## HOW TO ORDER

### A SPECIFY LUMINAIRE

Code	Power (LED)	Delivered lms	LPW	Type (A)	Type (B)
32 6110	14W	1311	93	14" (356mm)	
32 6112	20W	1865	95	18" (457mm)	
32 6114	28W	2592	94	24" (610mm)	
32 6116	47W	4333	92		36" (914mm)
32 6118	59W	5523	94		48" (1219mm)

### B SPECIFY CCT

30	3000K (min 80 CRI)
35	3500K (min 80 CRI)
40	4000K (min 80 CRI)

### C SPECIFY FASCIA

EQ	Style EQ
PM	Style PM

### D SPECIFY FINISH

WH	White
MS	Silver Metallic
MB	Metallic Bronze
SN	Satin Nickel
AB	Antique Brass
PB	Polished Brass
SB	Satin Brass
PC	Polished Chrome
OT	Other painted finish (RAL number required)

### E SPECIFY OPTIONS

PM	Perforated Mesh Accents (PM only)
VB	Vertical Bar (PM only)

### EXAMPLE CODE

326110/35/EQ/MS

### APPROVALS

