



BETACALCO

Beyond Brightness:

A Guide To Understanding Unified Glare Rating (UGR)

Prioritizing Visual Comfort in Modern Lighting Solutions

*Beta-Calco's SWITCH*

Introduction

With visual comfort becoming a cornerstone of modern architectural lighting design, the industry's focus has shifted from simple illumination to creating environments that enhance well-being and productivity. A critical yet often overlooked component of lighting quality is glare control. Poor glare management can cause discomfort, eye strain, headaches, and reduced concentration, underscoring the importance of effectively measuring and addressing this issue. The Unified Glare Rating (UGR) system offers a standardized method to measure, evaluate, and mitigate discomfort glare in interior lighting installations, ensuring spaces are not only bright but also visually comfortable. It does so by quantifying the relationship between luminaire brightness, background luminance, and viewing angles—factors essential to achieving both visual performance and occupant well-being.

As workplaces evolve to include more visually demanding tasks and extended screen time, understanding and applying lighting solutions with comfortable UGR values has never been more essential. This whitepaper examines the fundamentals of UGR, its significance in lighting design, practical applications in contemporary environments, and its contribution to creating comfortable, productive spaces that prioritize the human experience.

What Is Unified Glare Rating (UGR)?

The Unified Glare Rating (UGR) is an internationally recognized metric developed by the International Commission on Illumination (CIE) to quantify discomfort glare in interior lighting installations. Rather than being an inherent property of a single luminaire, it is a calculated value based on a specific lighting installation from a standard observer's viewpoint.

The UGR scale typically ranges from 10 (imperceptible glare) to 31 (intolerable glare), with lower values indicating greater visual comfort. The UGR Tables from DLC can have values between 5-40, with some Beta-Calco fixtures like the **BOGGLE** and **LE LOUVRE** with specific configurations able to go below a value of 10 from the tables. The calculation accounts for several factors that influence glare perception, including the luminance of light sources, their size and position relative to the observer, and the background luminance of the surrounding environment. This comprehensive approach allows for accurate prediction of glare levels in a given lighting setup, supports assessment of real-world visual comfort, and ensures that lighting configurations meet established comfort standards.

This empowers lighting designers to make informed decisions on fixture selection, placement, and optical control, resulting in optimized environments for specialized requirements. For instance, office settings require UGR levels below 19, while general areas may allow values up to 25.

UGR Value	Comfort Level/Glare Perception	Typical Applications
≤ 16	Excellent/Imperceptible	Technical Drawing, Detailed Inspection, CAD Workstations, Precision Tasks, Medical Facilities
≤ 19	Good/Slightly Perceptible	Offices, Reading, Writing, Classrooms, Computer Work
≤ 22	Acceptable/Perceptible	Reception Areas, General Industry, Craft Work, General Office Areas, Retail
≤ 25	Moderate/Mildly Uncomfortable	Lobbies, Corridors, Stairs, Heavy Industry, Occupied Storage Areas
> 25	Poor/Intolerable	Acceptable in Warehouses/Storage Rooms but generally avoided in Occupied Spaces

How Is UGR Calculated?

The UGR value is determined by a complex formula that considers several environmental factors. The key variables are:

L_b = Background Luminance (cd/m^2)

The brightness of the surrounding surfaces, such as walls and ceilings (affected by the room dimensions and reflective properties of the room surfaces)

L = Luminance of the Glare Source (cd/m^2)

The brightness of the light source as perceived by the eye (determined by the luminaire type, intensity, and photometric distribution)

ω = Solid Angle Subtended by the Source (Steradians)

Solid angle of each luminaire as seen from the observer, i.e. how "big" it looks (determined by luminaire size, position, and observer geometry)

P = Guth Position Index

Position index related to the source's position (determined by observer's position and viewing angle, i.e. location and line of sight of the observer in the space)

• The Formula

$$\text{UGR} = 8 \log_{10} \left[\frac{0.25}{L_b} \sum \left(\frac{L^2 \omega}{P^2} \right) \right]$$

Since UGR depends on the overall environment, an individual fixture does not have a fixed or intrinsic UGR value. Instead, most manufacturers provide tables showing a range of values based on different room configurations to help estimate glare levels for specific applications.



Why Is UGR Important in Modern Lighting?

Controlling glare is essential for creating functional and comfortable spaces.

The key benefits of designing with UGR in mind include:



Enhanced Visual Comfort and Productivity

Excessive glare causes visual fatigue, reduces concentration, and can lead to headaches and eye strain. Low-glare environments help prevent these effects, making spaces more comfortable for occupants, especially during prolonged or visually demanding tasks. This, in turn, supports better productivity and reduces the likelihood of errors.



Regulatory Compliance with Universal Standards and Improved Safety

Many lighting standards, such as EN 12464-1 for indoor workplaces, define maximum UGR limits for specific tasks and areas. For example, office work typically requires a $UGR \leq 19$, while other applications have different limits. Adhering to these standards enhances occupant safety and ensures visual clarity of potential hazards.



Screen-Based Work Considerations

With computer use now common across nearly all industries, UGR control has become increasingly critical. Glare from overhead lighting can cause screen reflections, forcing users to adjust posture or lower screen brightness, both of which can reduce comfort and productivity.



Improved Energy Efficiency

Achieving low UGR values often involves optical systems that enhance both visual comfort and energy performance. Well-designed luminaires with effective shielding and precise light distribution can reduce glare while improving overall efficiency.



International Standards

CIE 117:1995 – Discomfort Glare in Interior Lighting The foundational standard establishing UGR methodology and calculation procedures.

EN 12464-1:2011 – Light and Lighting – Lighting of Work Places – Part 1: Indoor Work Places European standard specifying UGR requirements for various interior applications.

IESNA Standards – North American guidelines providing UGR recommendations aligned with regional practices and preferences.

Application-Specific UGR Values (Ideal)

• Office Environments

UGR ≤ 19 for computer work areas,
 ≤ 22 for general office spaces



• Educational Facilities

UGR ≤ 19 for classrooms,
 ≤ 22 for corridors and common areas



• Healthcare Settings

UGR ≤ 16 for examination rooms,
 ≤ 19 for patient rooms



• Retail Spaces

UGR ≤ 22 for general areas,
 ≤ 25 for circulation zones



Some Beta-Calco products that can match the Low UGR requirements below 19 are our **MICRO FLARE**, **BRIDGE** and **RING BLADE** families among others.

Limitations of UGR

Limited Scope

UGR only measures Discomfort Glare and does not account for Disability Glare, Daylight Glare and veiling reflections (glare on screens). The calculation also does not address all comfort factors such as color quality, contrast ratios and distribution patterns.

Static by Nature

Since the calculation is only done for specific viewing positions, ie. fixed observer positions, this does not account for people moving through the space, different postures or actual user experience in dynamic environments. Along with that there are several assumptions made regarding background luminance (such as uniform ceilings and walls), luminaire specific limitations and a lack of adaptability over time that make the calculation static and point-based.

Variations Between Individuals

UGR is based on average observer responses, not accounting for age related differences or individual tolerance, which can significantly vary from individual to individual.

Complex and Inaccurate at Extremes

Calculating UGR involves complex formulas, specialized software, and extensive reference tables or manual verification, making the process time-consuming. Additionally, the calculation becomes less accurate for extremely low UGR values.

However, despite these limitations, UGR remains the most widely accepted metric for assessing discomfort glare. It is standardized across the industry, strongly supported by regulations, and represents a significant improvement over legacy methods such as the glare index. UGR also provides a reliable comparative basis for fixture selection. The best practice is to use it in conjunction with other key metrics, including contrast ratios, uniformity ratios, appropriate CRI/CCT combinations, and user feedback.

Future of UGR in Lighting Design

As lighting technology continues advancing, UGR considerations are becoming more sophisticated and integrated into the design process:

Advancing Modeling Tools

Modern lighting software keeps advancing and is continuing to provide real-time UGR calculations, enabling designers to optimize layouts and fixture selections during the design phase rather than after installation.

Human-Centric Considerations

Research into circadian lighting and visual comfort is expanding UGR applications beyond traditional discomfort glare to include broader wellness considerations.

Dynamic Lighting Systems

Smart lighting controls may eventually be able to adjust output levels and distribution patterns throughout the day at granular levels, maintaining optimal UGR values while supporting circadian rhythms and energy efficiency.

Material Innovation

Advanced optical materials and manufacturing techniques continue to improve the ability to achieve low UGR values while maintaining efficiency and aesthetic appeal.

Evolving Optical Design

Lighting technologies and optics are constantly evolving, with several technologies like Light Guide Plates (LGPs) and louvered designs becoming increasingly effective at reducing glare. This trend will only continue with attractive lighting becoming increasingly functional, especially in a UGR sense.



Conclusion

Unified Glare Rating represents more than a technical specification; it is a fundamental tool that reflects a growing commitment to human-centered lighting design. By understanding and applying proper UGR control principles, architects and designers can create environments that not only look refined but also support productivity, comfort, and well-being while meeting regulatory and sustainability goals.


The evolution of optical technologies, from traditional louvers to advanced light guide plate (LGP) systems, continues to expand the possibilities for achieving excellent UGR performance without compromising design intent or energy efficiency. As visual tasks become more demanding and work environments increasingly diverse, UGR will remain a cornerstone of lighting that serves human needs. Maintaining focus on UGR will be an essential building block in delivering solutions that are efficient, sustainable, and visually cohesive.

At Beta-Calco, this commitment to improving UGR performance aligns with our broader focus on optical innovation and human-centered design, supporting the creation of environments that are efficient, sustainable, and visually comfortable.


Achieving Visual Comfort: Beta-Calco's Low-Glare Products




BOGGLE



BRIDGE



LE LOUVRE




MICRO FLARE



RING BLADE



RING DISC



SWITCH

[Explore the Products Here](#)

References

- Akashi, Y., Muramatsu, R., & Kanaya, S. (1996). Unified Glare Rating (UGR) and subjective appraisal of discomfort glare. *Lighting Research & Technology*, 28(4), 199–206.
- Boyce, P. R. (2003). *Human factors in lighting* (2nd ed.). Taylor & Francis.
- Cuttle, C. (2015). *Lighting design: A perception-based approach*. Routledge.
- DesignLights Consortium. (n.d.). *Technical Requirements V5.1: Understanding Unified Glare Rating (UGR)*.
- DiLaura, D. L., Houser, K. W., Mistrick, R. G., & Steffy, G. R. (Eds.). (2011). *The lighting handbook: Reference and application* (10th ed.). Illuminating Engineering Society.
- Einhorn, H. D. (1998). Unified glare rating (UGR): Merits and application to multiple sources. *Lighting Research & Technology*, 30(2), 89–93.
- European Committee for Standardization. (2011). EN 12464-1:2011 Light and lighting – Lighting of work places – Part 1: Indoor work places. CEN.
- Illuminating Engineering Society. (2018). IES RP-1-12 American National Standard Practice for Office Lighting. IES.
- International Commission on Illumination (CIE). (1995). CIE 117:1995 Discomfort glare in interior lighting. CIE Central Bureau.
- International Commission on Illumination (CIE). (2010). CIE 190:2010: Calculation and presentation of unified glare rating tables for indoor lighting luminaires. CIE Central Bureau.
- International Commission on Illumination (CIE). (2017). CIE 231:2017: Discomfort caused by glare from luminaires with a non-uniform source luminance. CIE Central Bureau.
- National Electrical Manufacturers Association, Luminaire Section. (2021). *White Paper on Unified Glare Rating (UGR) (NEMA LS 20001-2021)*.
- Sawicki, D., et al. (2016). The unified semantic glare scale for GR and UGR indexes. *Light & Engineering*, 24(3).
- Veitch, J. A. (2001). Psychological processes influencing lighting quality. *Journal of the Illuminating Engineering Society*, 30(1), 124–140.
- Wienold, J., & Christoffersen, J. (2006). Evaluation methods and development of a new glare prediction model for daylight environments with the use of CCD cameras. *Energy and Buildings*, 38(7), 743–757.