



GENERAL SPECIFICATION

Housing: Die-cast aluminum.

External Screws: Stainless steel.

Lens: 6mm/0.25" tempered glass.

Gaskets: One piece silicone.

Finish: Silver powder coated RAL9006 or black powder coated.

Drivers: HPF, electronic for 120-277V (EU-240V).

Minimum Starting Temperature: -30°C for LEDs.


Conduit entry: PG11 gland for 11mm/0.625" DIA cable.

Delivered Lumens: Delivered lumens and LPW based on 3000K (min 80 CRI).


MOUNTING & OPTICS



Ext-Ceiling/Canopy



81 0348-14W-40
DEG



81 0347-14W-8 DEG

HOW TO ORDER

A SPECIFY L

Code:	Power (LED):	Beam:	Delivered lms:
81 0347	14W	8°	1049
81 0348	14W	40°	1049

B SPECIFY CCT

30	3000K (min 80 CRI)
40	4000K (min 80 CRI)

C SPECIFY FINISH

BL	Black
GR	Gray RAL 9006


D SPECIFY DIMMING

DB	Dimming (0-10V, 10%)
----	----------------------

EXAMPLE SPECIFICATION CODE

810347/30/BL

DIMENSIONAL DIAGRAMS



APPROVALS

