



GENERAL SPECIFICATION

Body: Aluminium.

Finish: Powder coated.

Diffusers: Frosted Polycarbonate.

Drivers: Remote, HPF electronic drivers for 120-277V (EU-240V), 0-10V, 1% dimming standard. Wire size 18 AWG - max distance (from fixture to drivers) 40', wire size 16 AWG - max distance 60', wire size 14 AWG - max distance 90'. Drivers must be accessible after installation.

L70 @25deg C: > 50,000 hrs.

Delivered Lumens: Delivered lumens & LPW based on 3000K (min 80 CRI) for White LEDs only.


MOUNTING & OPTICS




Ceiling Direct/Indirect




Ceiling Direct




Wall Direct/Indirect




Wall Direct




98 3405




98 3410




98 3420




98 3430




98 3440




98 3505




98 3510



95 3520



98 3530



98 3540

HOW TO ORDER

A SPECIFY LUMINAIRE

Code:	Diameter (A):	Power (LED):	Light Distribution:	Delivered lms:	LPW:
98 3405	610mm/24"	26W	Direct	3131	120
98 3410	889mm/35"	39W	Direct	4689	120
98 3420	1219mm/48"	51W	Direct	6225	122
98 3430	1524mm/60"	70W	Direct	8574	122
98 3440	1854mm/73"	83W	Direct	10102	122
98 3505	610mm/24"	31W	Direct/Indirect	3767	122
98 3510	889mm/35"	47W	Direct/Indirect	5628	120
98 3520	1219mm/48"	62W	Direct/Indirect	7469	120
98 3530	1524mm/60"	84W	Direct/Indirect	10292	123
98 3540	1854mm/73"	100W	Direct/Indirect	12125	121

B SPECIFY CCT/COLOR (DIRECT)

D30	3000K (min 80 CR)
D35	3500K (min 80 CR)
D40	4000K (min 80 CR)
DRD	Red
DGN	Green
DBL	Blue

C SPECIFY CCT/COLOR (INDIRECT)

N30	3000K (min 80 CR)
N35	3500K (min 80 CR)
N40	4000K (min 80 CR)
NRD	Red
NGN	Green
NBL	Blue


D SPECIFY FINISH

BL	Black
MS	Metallic Silver
WH	White
Z1	Wood Grain - Light Cherry
Z2	Wood Grain - Dark Walnut

EXAMPLE SPECIFICATION CODE

983405/D35/N35/WH

DIMENSIONAL DIAGRAMS



APPROVALS

