

SENTINEL™ - WALL

Project Name:	Fixture Type:
Fixture Code:	Quantities:





SENTINEL™ - WALL



# SENTINEL™ - WALL

**SENTINEL** stands ready and secures the way, delivering a powerful omnidirectional light reinforced with optional uplight and downlight in either narrow or wide beam angles.

## GENERAL SPECIFICATION

### Housing

Die-cast and extruded (low copper) aluminium. Front housing hinges open for access and secures via a bolt hidden behind a spring loaded flap.

### Gaskets

One piece silicone.

### Drivers

HPF electronic, 120-277V (EU-240V), 0-10V Dimming (equal to or less than 10%) for Direct Light Only. Up/Down light non-dimming.

### Diffuser

UV stabilised polycarbonate.

### Remote Emergency

Emergency option provides a 1.5 hour (3 hours for EU) emergency lighting facility. The remote system includes the inverter module, NiCad batteries and a remote wall/ceiling LED charge indicator and test switch (NA only) Maximum distance between wall/ceiling plate and luminaire is 4.5m/15'. Test switch fits a single gang box (not supplied).

### Finish

Exterior grade, metallic powder coated paint.

### Reflector

Aluminium, white powder coated.

### Mechanical

Mounts directly over a standard electrical junction box (by others - North America only).

### Minimum Starting Temperature

-20°C.

### Delivered Lumens

Delivered lumens & LPW based on 3000K (min 80 CRI).

## MOUNTING & OPTICS



Ext-Wall

# SENTINEL™ - WALL

## HOW TO ORDER

### A. LUMINAIRE

<b>322755</b> 27" Type, 3000K, 1124 lms	<b>322756</b> 27" Type, 4000K, 1205 lms	<b>325155</b> 51.2", 3000K, 2269 lms	<b>325156</b> 51.2", 4000K, 2430 lms
---	---	--------------------------------------	--------------------------------------

### B. OPTIONAL DOWNLIGHT MODULE ILLUMINATION

<b>SDL1</b> 1 x 2W Down, Narrow, 3000K	<b>SDL2</b> 1 x 4W Down, Wide, 3000K	<b>SDL3</b> 1 x 2W Down, Narrow, 4000K	<b>SDL4</b> 1 x 4W Down, Wide, 4000K
--	--------------------------------------	--	--------------------------------------

### C. OPTIONAL UPLIGHT MODULE ILLUMINATION

<b>SUL1</b> 1 x 2W Up, Narrow, 3000K	<b>SUL2</b> 1 x 4W Up, Wide, 3000K	<b>SUL3</b> 1 x 2W Up, Narrow, 4000K	<b>SUL4</b> 1 x 4W Up, Wide, 4000K
--------------------------------------	------------------------------------	--------------------------------------	------------------------------------

### D. FINISH

<b>BL</b> Black Metallic Textured	<b>MS</b> Silver Metallic Textured	<b>BM</b> Bronze Metallic Textured
-----------------------------------	------------------------------------	------------------------------------

### E. OPTIONS

<b>VB</b> Vertical Bar	<b>RE</b> Remote Emergency for Front LED only (max distance 10ft, 120/277V)
------------------------	---

# SENTINEL™ - WALL

## TECHNICAL DATA

### LUMINAIRE

Code	322755	322756	325155	325156
Power (LED)	14W	14W	28W	28W
CCT	3000K	4000K	3000K	4000K
Delivered lms	1124	1205	2269	2430
LPW	80	86	81	87
Type (A)	27"	27"		
Type (B)			51.2"	51.2"

### OPTIONAL DOWN MODULE

Code	SDL1	SDL2	SDL3	SDL4
Power (LED)	1 x 2W Down	1 x 4W Down	1 x 2W Down	1 x 4W Down
Beam	Narrow	Wide	Narrow	Wide
CCT	3000K	3000K	4000K	4000K
Delivered lms	121	170	150	212

### OPTIONAL UP MODULE

Code	SUL1	SUL2	SUL3	SUL4
Power (LED)	1 x 2W Up	1 x 4W Up	1 x 2W Up	1 x 4W Up
Beam	Narrow	Wide	Narrow	Wide
CCT	3000K	3000K	4000K	4000K
Delivered lms	121	170	150	212

## FINISH



Black Metallic Textured   Silver Metallic Textured   Bronze Metallic Textured

## APPROVALS



SENTINEL™ - WALL

DIMENSIONAL DIAGRAMS

