

PATH™ - BOLLARDS

Project Name:	Fixture Type:
Fixture Code:	Quantities:




PATH™ - BOLLARDS

GENERAL SPECIFICATION

Housing	External Screws
Die-cast and extruded aluminium.	Stainless steel.
Lens	Gaskets
Clear polycarbonate.	One piece silicone.
Finish	Drivers
Silver powder coated RAL9006 or black powder coated.	HPF, electronic for 120-277V (EU-240V).
Cable entry	Mounting
M20 cable gland.	Anchorage rods required for concrete.
Delivered Lumens	
Delivered lumens & LPW based on 3000K (min 80 CRI).	

MOUNTING & OPTICS



Ext-Bollards

PATH™ - BOLLARDS

HOW TO ORDER

A. LUMINAIRE

8307501 A Type, 933 lms	8307511 B Type, 933 lms	8307515 C Type, 933 lms
--------------------------------	--------------------------------	--------------------------------

B. CCT

30 3000K (min 80 CRI)	40 4000K (min 80 CRI)
------------------------------	------------------------------

C. FINISH

BL Black	GR Light Gray RAL 9006
-----------------	-------------------------------

D. ANCHORAGE BASE

8307599/BL Anchorage base for poured concrete (Type A & B)	8307599/GR Anchorage base for poured concrete (Type A & B)	8307580/BL Anchorage base for poured concrete (Type C)	8307580/GR Anchorage base for poured concrete (Type C)
---	---	---	---

E. LIGHT SHIELDS

8307590/BL Lighting Shields (qty 2)	8307590/GR Lighting Shields (qty 2)
--	--

F. DIMMING

DB Dimming (0-10V, 10%)

PATH™ - BOLLARDS

TECHNICAL DATA

LUMINAIRE

Code	8307501	8307511	8307515
Power (LED)	14W	14W	14W
Delivered lms	933	933	933
Type	A	B	C

APPROVALS



PATH™ - BOLLARDS

DIMENSIONAL DIAGRAMS

