Project Name: Fixture Type:

Fixture Code: Quantities:











Our dual circuit luminaire delivers high efficiency diffused, spot and direct light, allowing you to transition from general ambient to mood lighting. Available in two sizes 18" & 24", the **WARP** family offers two styles of pendant plus a ceiling mounted version. The color temperature of each light source can be individually selected to deliver an effect best suited to the application. New to the WARP are a wide array of contemporary decorative colors to accent your architectural scene.

GENERAL SPECIFICATION

Body

Aluminum and steel.

Suspension

Steel cables.

Drivers

HPF electronic drivers for 120-277V, 347V, (EU-240V)

Mechanical

Luminaires mount directly to a J box (by others - North America only).

Integral emergency system

Emergency option provides a 1.5 hour (3 hours for EU) emergency lighting facility. The self contained system includes the inverter module, NiCad batteries, LED charge indicator and test switch (NA only). Integral emergency EU luminaires have a 10.5" (270mm) DIA x 2" (48mm) height canopy with LED charge indicator. Not available with a 347V supply.

Delivered lumens

Delivered lumens & LPW based on 4000K (min 80 CRI).

Design

US Pat. No. D897,589

MOUNTING & OPTICS



Suspended Direct

Canopy finish

Powder coated.

Power cable

Silver braided.

Diffuser

Acrylic.

L70 @25°C

> 50,000 hrs.

Remote emergency

Emergency option provides a 1.5 hour (3 hours for EU) emergency lighting facility. The remote system includes the inverter module, NiCad batteries and a remote wall/ceiling LED charge indicator and test switch (NA only) Maximum distance between wall/ceiling plate and luminaire is 15' (4.5m). Test switch fits a single gang box (not supplied).

Approvals

Damp Location (Indoor use only).

Designed by

Serge Cornelissen.

HOW TO ORDER

A. LUMINAIRE

WAHP1P18 18", 3300 lms **WAHP1P24** 24", 4900 lms

B. LUMENS

LMA0200 2000 lm **LMA0330** 3300 lm **LMA0490** 4900 lm ¹

C. CRI

CR80 CRI 80+

D. CCT

CTA27 2700K **CTA30** 3000K **CTA35** 3500K **CTA40** 4000K

E. VOLTAGE

V1 120/277V **V2** 240V ¹ **V3** 347V ²

F. DIMMING

DA01 0-10V Dimming 1.0% **DA02** 0-10V Dimming 0.1% ¹ **DA20** DALI Dimming 0.1% ¹ **DA21** DALI Dimming 1.0% ¹

DA30 DSI/switchDim ^{1 2}

G. FIXTURE FINISH

FA01 WhiteFA02 Black Metallic - TexturedFA20 Silver Metallic - TexturedFA25 Gold Metallic - TexturedFA45 Copper MetallicFA44 Midnight Blue Metallic - TexturedFA46 Charcoal Metallic - TexturedFA47 Bronze Metallic - Textured

FA52 Champagne Metallic **FA53** Red Metallic - Textured

H. CANOPY FINISH

CF01 White CF02 Black Metallic - Textured CF25 Gold Metallic - Textured CF25 Gold Metallic - Textured CF26 Coppor Metallic - T

I. EMERGENCY

E0 Not required **E1** Emergency system - Integral **E2** Emergency system - Remote

J. DOWNLIGHT SPOT

DL00 Not required **DL27** Downlight 28W, 2700K (1730 **DL30** Downlight 28W, 3000K (1799 delivered lms) **DL35** Downlight 28W, 3500K (1854 delivered lms)

DL40 Downlight 28W, 4000K (1858

delivered lms)

CIRCUITS

CS1 Single circuit **CS2** Dual circuit

¹ Available for WAHP1P24 only.

¹ Not available in North America.

² Available with DAO1 dimming only.

¹ Not available with 347V.

² Not available in North America.

TECHNICAL DATA

LUMINAIRE

Code	WAHP1P18	WAHP1P24
Diameter (A)	18"	24"
Light Direction	Direct	Direct
Wattage	22W	34W
Delivered Ims	3300	4900
LPW	146	145
Height (B)	6"	6.5"

FIXTURE FINISH





Textured



Textured



Textured





Textured



Charcoal Metallic -

Textured



Textured





Champagne Metallic Red Metallic -Textured

CANOPY FINISH



















Silver Metallic -Textured

Gold Metallic -Textured

Midnight Blue Metallic -Textured

Copper Metallic

Charcoal Metallic -Bronze Metallic -Textured Textured

Champagne Metallic

Red Metallic -Textured

APPROVALS











DIMENSIONAL DIAGRAMS

