

ARKO EX™ - MODERN CLASSICS EXTERIOR

| | |
|---------------|---------------|
| Project Name: | Fixture Type: |
| Fixture Code: | Quantities: |



ARKO EX™ - MODERN CLASSICS EXTERIOR



ARKO EX™ - MODERN CLASSICS EXTERIOR

A facade light with a curved acrylic diffuser, designed for tall walls. Once illuminated, two parallel bars are silhouetted, giving the illusion of a slender minimalist frame, ideal for accenting modern architecture.

GENERAL SPECIFICATION

Cover

Extruded aluminium profile.

Finish

Silver Metallic powder coated.

Remote emergency system

Emergency option provides a 1.5 hour emergency lighting facility. The remote system includes the inverter module, NiCad batteries and a remote wall/ceiling LED charge indicator and test switch (maximum distance between wall/ceiling plate and luminaire is 4.5m/15'). Test switch fits a single gang box (not supplied).

Minimum Starting Temperature

-20°C.

Main body

Stainless steel and aluminium, retained by stainless steel screws.

Diffuser

Extruded opal acrylic.


Drivers

HPF, electronic, 0-10V, equal to or less than 10% dimming standard.


Delivered Lumens

Delivered lumens & LPW based on 3000K (min 80 CRI).

MOUNTING & OPTICS



Ext-Wall



General Diffuse



ARKO EX™ - MODERN CLASSICS EXTERIOR

HOW TO ORDER

A. LUMINAIRE

| | | | |
|-------------------------------|-------------------------------|-------------------------------|-------------------------------|
| 317080 24.5", 1095 lms | 317082 24.5", 2000 lms | 317085 48.2", 1938 lms | 317087 48.2", 3840 lms |
|-------------------------------|-------------------------------|-------------------------------|-------------------------------|

B. CCT

| | | |
|------------------------------|------------------------------|------------------------------|
| 30 3000K (min 80 CRI) | 35 3500K (min 80 CRI) | 40 4000K (min 80 CRI) |
|------------------------------|------------------------------|------------------------------|

C. DIFFUSER ACCENT

| | |
|----------------|-----------------------|
| OP Opal | CB Cobalt Blue |
|----------------|-----------------------|

D. CUSTOM FINISHES

| | |
|---|--|
| F39 Other painted finish (RAL number required) | F40 Other Non-RAL painted finish (sample chip required) |
|---|--|

F39 & F40 have a one time set-up charge regardless of quantity.

E. EMERGENCY

| |
|---|
| RE Remote Emergency (max distance 25 ft, 120/277V) |
|---|

Dimming is not available when using RE (Remote Emergency)

ARKO EX™ - MODERN CLASSICS EXTERIOR

TECHNICAL DATA

LUMINAIRE

| Code | 317080 | 317082 | 317085 | 317087 |
|---------------|--------|--------|--------|--------|
| Power (LED) | 16W | 28W | 28W | 56W |
| Delivered lms | 1095 | 2000 | 1938 | 3840 |
| LPW | 72 | 74 | 71 | 71 |
| Height (A) | 24.5" | 24.5" | 48.2" | 48.2" |
| Weight | 8.8lb | 8.8lb | 18.4lb | 18.4lb |

APPROVALS



ARKO EX™ - MODERN CLASSICS EXTERIOR

DIMENSIONAL DIAGRAMS

