AXALIS TL™ - WALL SURFACE

Project Name:

Fixture Type:

Fixture Code:

Quantities:



© 2026 Beta-Calco Inc. Specifications are subject to change without notice

AXALIS TL™ - WALL SURFACE

GENERAL SPECIFICATION

Body and trim
Steel and extruded aluminum. Trim claws, die cast alloy.

Finish
Back plate, powder coated gloss white. Side trim, brushed aluminum. Trim claws, as listed.


Diffuser
Opal acrylic.

Dust covers
Opal Polycarbonate.

Drivers
HPF, electronic for 120-277V (EU-240V), 0-10V dimming (10%) standard.

Delivered Lumens
Delivered lumens & LPW based on 3000K (min 80 CRI).

OPTICS & FEATURES


Wall


General Diffuse

© 2026 Beta-Calco Inc. Specifications are subject to change without notice

AXALIS TL™ - WALL SURFACE

HOW TO ORDER

A. LUMINAIRE

701110 701110

701120 701120

701130 701130

B. CCT

30 3000K (min 80 CRI)

35 3500K (min 80 CRI)

40 4000K (min 80 CRI)

C. OPTIONS

TM Trim Claws, Silver Metallic

TB Trim Claws, Black Chrome

TC Trim Claws, Polished Chrome

TP Trim Claws, Polished Brass

TS Trim Claws, Satin Brass

TECHNICAL DATA

LUMINAIRE

Code	701110	701120	701130
Power (LED)	16W	24W	32W
Delivered lms	1244	1877	2462
LPW	80	79	80
Height (A)	15"	18"	23"


APPROVALS

ADA

© 2026 Beta-Calco Inc. Specifications are subject to change without notice

AXALIS TL™ - WALL SURFACE

DIMENSIONAL DIAGRAMS



© 2026 Beta-Calco Inc. Specifications are subject to change without notice