

# AXALIS TL™ - WALL SURFACE

Project Name:

Fixture Type:

Fixture Code:

Quantities:



# AXALIS TL™ - WALL SURFACE

## GENERAL SPECIFICATION

### Body and trim

Steel and extruded aluminum. Trim claws, die cast alloy.

### Diffuser

Opal acrylic.

### Drivers

HPF, electronic for 120-277V (EU-240V), 0-10V dimming (10%) standard.

### Finish

Back plate, powder coated gloss white. Side trim, brushed aluminum. Trim claws, as listed.


### Dust covers

Opal Polycarbonate.


### Delivered Lumens

Delivered lumens & LPW based on 3000K (min 80 CRI).

## OPTICS & FEATURES



Wall



General Diffuse

# AXALIS TL™ - WALL SURFACE

## HOW TO ORDER

### A. LUMINAIRE

**701110** 701110

**701120** 701120

**701130** 701130

### B. CCT

**30** 3000K (min 80 CRI)

**35** 3500K (min 80 CRI)

**40** 4000K (min 80 CRI)

### C. OPTIONS

**TM** Trim Claws, Silver Metallic

**TB** Trim Claws, Black Chrome

**TC** Trim Claws, Polished Chrome

**TP** Trim Claws, Polished Brass

**TS** Trim Claws, Satin Brass

## TECHNICAL DATA

### LUMINAIRE

Code	701110	701120	701130
Power (LED)	16W	24W	32W
Delivered lms	1244	1877	2462
LPW	80	79	80
Height (A)	15"	18"	23"

## APPROVALS



# AXALIS TL™ - WALL SURFACE

## DIMENSIONAL DIAGRAMS

