

AXALIS™ - SUSPENDED

Project Name:

Fixture Type:

Fixture Code:

Quantities:



betacalco.com | +1 416-531-9942 | sales@betacalco.com

© 2026 Beta-Calco Inc. Specifications are subject to change without notice

Jan 9, 2026

Page 1 of 4

AXALIS™ - SUSPENDED

GENERAL SPECIFICATION

Body and trim

Steel and aluminum.

Suspension

One stainless steel aircraft cable.

Power cable

Silver braided.

Finish

Silver anodized.

Diffusers

Opal acrylic with an etched finish.

Drivers

Luminaires supplied with HPF electronic drivers, 120/277V (EU-240V). 0-10V dimming standard (10%).

Mechanical

Mounts directly over a junction box (by others - North America only).

Integral Emergency system

Emergency option provides a 1.5 hour (3 hours for EU) emergency lighting facility. The self contained system includes the inverter module, NiCad batteries, LED charge indicator and test switch (NA only). Not available with a 347V supply.


L70 @ 25°C (77°F)

> 50,000 hrs.


Delivered Lumens

Delivered lumens and LPW based on 3000K (min 80 CRI).


OPTICS & FEATURES



Suspended 2 sides



Suspended 3 sides



General Diffuse



Spot Only



AXALIS™ - SUSPENDED

HOW TO ORDER

A. LUMINAIRE

436052 18", 3659 lms
436071 49", 8635 lms

436054 18", 4561 lms

436056 27", 5321 lms

436058 27", 7300 lms

B. CCT

30 3000K (min 80 CRI)

35 3500K (min 80 CRI)

40 4000K (min 80 CRI)

C. DOWNLIGHT

X1 Xacara downlight 28W LED 3000K
(2587lm delivered)

X2 Xacara downlight 28W LED 3500K
(2665lm delivered)

X3 Xacara downlight 28W LED 4000K
(2690lm delivered)

D. EMERGENCY

EM Integral Emergency

TECHNICAL DATA

LUMINAIRE

Code	436052	436054	436056	436058	436071
Power (LED)	48W	60W	72W	96W	115W
Delivered lms	3659	4561	5321	7300	8635
LPW	78	78	76	76	75
Height (A)	18"	18"	27"	27"	49"
Height (B)	1"	1"	1"	1"	1.8"

APPROVALS



AXALIS™ - SUSPENDED

DIMENSIONAL DIAGRAMS

