

MASSIO™ - WALL SURFACE EXTERIOR

Project Name:

Fixture Type:

Fixture Code:

Quantities:



MASSIO™ - WALL SURFACE EXTERIOR

GENERAL SPECIFICATION

Body and trim

Low copper, die-cast aluminum highly resistant to oxidation.

Gasket

Silicone.

External screws

A4 stainless steel treated with highly antioxidant water-repellent lubricating solution to ensure easy opening.

Drivers

HPF, electronic for 120V/277V.

Delivered Lumens

Delivered lumens & LPW based on 3000K (min 80 CRI).

Lens

3mm/0.12" tempered glass/convex lens.

Finish

Powder coated.

Cable entry

M20 gland for DIA 8-12mm/0.2-0.47" cables.

Mechanical

For surface mounting.

OPTICS & FEATURES



Ext-Wall Downlight Ext-Wall Up/Down

MASSIO™ - WALL SURFACE EXTERIOR

HOW TO ORDER

A. LUMINAIRE

8308140 8308140

8308134 8308134

8308130 8308130

8308136 8308136

8308132 8308132

8308138 8308138

B. CCT

30 3000K (min 80 CRI)

40 4000K (min 80 CRI)

C. FINISH

BL Black

AG Anthracite Gray

GR Gray RAL 9006

D. DIMMING

DB Dimming 0-10V, 10%

Dimming not available for 830 8140

TECHNICAL DATA

LUMINAIRE

Code	8308140	8308130	8308132	8308138	8308134	8308136
Power (LED)	6W	26W	26W	16W	26W	6W+18W
Distribution	2° x 35° Asymmetrical Narrow	32° Medium Down	2 x 32° Medium Up/Down	4 x (2°x35°) Asymmetrical Narrow	4 x 32° Medium	Spot Up/Flood Down
Delivered lms	31	361	898	118	449	---

APPROVALS



MASSIO™ - WALL SURFACE EXTERIOR

DIMENSIONAL DIAGRAMS

