

# MASSIO™ - WALL SURFACE EXTERIOR

Project Name:

Fixture Type:

Fixture Code:

Quantities:



# MASSIO™ - WALL SURFACE EXTERIOR

## GENERAL SPECIFICATION

### Body and trim

Low copper, die-cast aluminum highly resistant to oxidation.

### Gasket

Silicone.

### External screws

A4 stainless steel treated with highly antioxidant water-repellent lubricating solution to ensure easy opening.

### Drivers

HPF, electronic for 120V/277V.

### Delivered Lumens

Delivered lumens & LPW based on 3000K (min 80 CRI).

### Lens

3mm/0.12" tempered glass/convex lens.

### Finish

Powder coated.

### Cable entry

M20 gland for DIA 8-12mm/0.2-0.47" cables.

### Mechanical

For surface mounting.

## OPTICS & FEATURES



Ext-Wall Downlight



Ext-Wall Up/Down

# MASSIO™ - WALL SURFACE EXTERIOR

## HOW TO ORDER

### A. LUMINAIRE

**8308140** 8308140  
**8308134** 8308134

**8308130** 8308130  
**8308136** 8308136

**8308132** 8308132

**8308138** 8308138

### B. CCT

**30** 3000K (min 80 CRI)

**40** 4000K (min 80 CRI)

### C. FINISH

**BL** Black

**AG** Anthracite Gray

**GR** Gray RAL 9006

### D. DIMMING

**DB** Dimming 0-10V, 10%

Dimming not available for 830 8140

## TECHNICAL DATA

### LUMINAIRE

Code	<b>8308140</b>	<b>8308130</b>	<b>8308132</b>	<b>8308138</b>	<b>8308134</b>	<b>8308136</b>
Power (LED)	6W	26W	26W	16W	26W	6W+18W
Distribution	2° x 35° Asymmetrical Narrow	32° Medium Down	2 x 32° Medium Up/Down	4 x (2°x35°) Asymmetrical Narrow	4 x 32° Medium	Spot Up/Flood Down
Delivered lms	31	361	898	118	449	---

## APPROVALS



# MASSIO™ - WALL SURFACE EXTERIOR

## DIMENSIONAL DIAGRAMS

