

# BLADE II™ - WALL SURFACE EXTERIOR

Project Name:

Fixture Type:

Fixture Code:

Quantities:



# BLADE II™ - WALL SURFACE EXTERIOR

## GENERAL SPECIFICATION

### Body and trim

Die-cast aluminium.

### Front fascia

Injection molded plastic, UV stabilised, painted RAL9006. Front fascia can be custom painted to special order (Consult factory).

### Drivers

HPF, electronic for 120-277V (EU-240V).

### Delivered Lumens

Delivered lumens & LPW based on 3000K (min 80 CRI).

### Finish

Silver powder coated, RAL9006.

### Gasketing

Heat resistant silicone.

### Minimum Starting Temperature

-30°C.

## MOUNTING & OPTICS



Ext-Wall Up/Down



Narrow



Medium



Twin Narrow

# BLADE II™ - WALL SURFACE EXTERIOR

## HOW TO ORDER

### A. LUMINAIRE

**662004** 662004                      **662014** 662014                      **662024** 662024                      **662034** 662034  
**662044** 662044

### B. CCT

**30** 3000K (min 80 CRI)                      **40** 4000K (min 80 CRI)                      **B** Blue

### C. DIMMING

**DB** Dimming 0-10V (10%)

## TECHNICAL DATA

### LUMINAIRE

Code	662004	662014	662024	662034	662044
2 x 3W	Narrow Beam	Medium/Narrow Beam	Medium Beam	Twin/Narrow Beam	Twin Beam
Beam	10°	40°/10°	40°	2x5°/10°	2x5°
Delivered lms	2 x 236	2 x 236	2 x 236	2 x 236	2 x 236

## APPROVALS



# BLADE II™ - WALL SURFACE EXTERIOR

## DIMENSIONAL DIAGRAMS

