

# BLADE III™ - WALL SURFACE EXTERIOR

Project Name:

Fixture Type:

Fixture Code:

Quantities:



# BLADE III™ - WALL SURFACE EXTERIOR

## GENERAL SPECIFICATION

### Body and trim

Die-cast aluminium.

### Finish

Silver powder coated, RAL9006.

### Front fascia

Injection molded plastic, UV stabilised, painted RAL9006. Front fascia can be custom painted to special order (Consult factory).

### Gasketing

Heat resistant silicone.

### Drivers

HPF, electronic for 120-277V (EU-240V).

### Minimum Starting Temperature

-30°C.

### Delivered Lumens

Delivered lumens & LPW based on 3000K (min 80 CRI).

## MOUNTING & OPTICS



Ext-Wall Up/Down



# BLADE III™ - WALL SURFACE EXTERIOR

## HOW TO ORDER

### A. LUMINAIRE

**663004** 663004                      **663014** 663014                      **663024** 663024                      **663034** 663034

### B. CCT

**30** 3000K (min 80 CRI)                      **40** 4000K (min 80 CRI)                      **B** Blue

### C. DIMMING

**DB** Dimming 0-10V, 10%

## TECHNICAL DATA

### LUMINAIRE

Code	663004	663014	663024	663034
3 x 3W	Narrow Beam	Twin Beam	Medium Beam	Medium/Narrow Beam
Beam	10°	2x5°	40°	40°/10°
Delivered lms	3 x 236	3 x 236	3 x 236	3 x 236

## APPROVALS



# BLADE III™ - WALL SURFACE EXTERIOR

## DIMENSIONAL DIAGRAMS

