

# BLADE III™ - WALL SURFACE EXTERIOR

Project Name:

Fixture Type:

Fixture Code:

Quantities:



# BLADE III™ - WALL SURFACE EXTERIOR

## GENERAL SPECIFICATION

### Body and trim

Die-cast aluminium.

### Finish

Silver powder coated, RAL9006.

### Front fascia

Injection molded plastic, UV stabilised, painted RAL9006. Front fascia can be custom painted to special order (Consult factory).

### Gasketing

Heat resistant silicone.

### Drivers

HPF, electronic for 120-277V (EU-240V).

### Minimum Starting Temperature

-30°C.

### Delivered Lumens

Delivered lumens & LPW based on 3000K (min 80 CRI).

## OPTICS & FEATURES



Ext-Wall Up/Down

# BLADE III™ - WALL SURFACE EXTERIOR

## HOW TO ORDER

### A. LUMINAIRE

**663004** 663004

**663014** 663014

**663024** 663024

**663034** 663034

### B. CCT

**30** 3000K (min 80 CRI)

**40** 4000K (min 80 CRI)

**B** Blue

### C. DIMMING

**DB** Dimming 0-10V, 10%

## TECHNICAL DATA

### LUMINAIRE

Code	<b>663004</b>	<b>663014</b>	<b>663024</b>	<b>663034</b>
<b>3 x 3W</b>	Narrow Beam	Twin Beam	Medium Beam	Medium/Narrow Beam
<b>Beam</b>	10°	2x5°	40°	40°/10°
<b>Delivered lms</b>	3 x 236	3 x 236	3 x 236	3 x 236

## APPROVALS



# BLADE III™ - WALL SURFACE EXTERIOR

## DIMENSIONAL DIAGRAMS

