
BOGGLE™

SHORT SPECIFICATION SHEET



FIXTURE TYPE

FIXTURE CODE

QUANTITIES

1 HOW TO ORDER

LUMINAIRE

BGGR1R Direct

One power cord for every 50 linear feet.

LENGTH OF RUN

Order in 2ft increments.

SFA_ _ _ _

MAX LENGTH PER SECTION

SL02 2ft [1]
SL04 4ft
SL06 6ft
SL08 8ft
SL10 10ft
SL12 12ft

[1] Not available with 200 lm/ft.
* You can select the preferred maximum length per segment, to account for transportation and building constraints. Example: If a 40ft run is required and SL12 (12ft) is selected, we would provide 4x 10ft segments. For special requirements, please contact sales@betacalco.com.
* Review the Linear Length Configurations document for each length of run.

LOUVER

BL1 White Glossy
BL2 Black Glossy
BL3 White Matte
BL4 Black Matte

All data shown based on max values, consult Performance Data download for more details.

LM/FT

LPF020 200 lm/ft
LPF040 400 lm/ft
LPF060 600 lm/ft
LPF080 800 lm/ft
LPF100 1000 lm/ft

CRI

CR90 CRI 90+

CCT

CTA27 2700K
CTA30 3000K
CTA35 3500K
CTA40 4000K
CTA60 Tunable White

© 2026 Beta-Calco Inc. Specifications are subject to change without notice

BOGGLE™ - RECESSED CONTINUOUS
SHORT SPECIFICATION SHEET

VOLTAGE

V1 120/277V

V2 240V [1]

V3 347V [2]

V4 Low Voltage [3]

[1] Not available in North America. [2] Only available with DA01 dimming. [3] Only available with DA45 dimming.

DIMMING

DA01 0-10V Dimming 1.0%

DA02 0-10V Dimming 0.1% [1]

DA20 DALI Dimming 0.1% [1]

DA21 DALI Dimming 1.0% [1]

DA23 DALI DT8 Dimming 0.1% - Tunable White [1] [2]

DA45 PoE [3]

[1] Not available with V3.
[2] Only available with Tunable White.
[3] Only available with V4.

CEILING TYPE & TRIM

RT1 Tegular T-Bar [1]

RT2 Lay-In T-Bar [1]

RT3 Trimless [3]

RT4 Trim [3]

[1] Fixture designed to fit into a 9/16" or 15/16" standard tegular grid T-bar and through tile mount. Dimensions are nominal for grid ceiling fixtures. All fixture metalwork is white.
[2] Fixture designed to fit into a 9/16" or 15/16" standard grid T-bar and through tile mount. Dimensions are nominal for grid ceiling fixtures. All fixture metalwork is white.
[3] Fixture designed for drywall ceilings.

CEILING TRIM FINISH

FA00 Not required

FA01 White - Textured [1]

FA02 Black Metallic Textured [1]

[1] Required for RT4 only.

EMERGENCY

E0 Not required

E1 Emergency system - Integral [1] [2]

E3 Emergency generated circuit - Remote [1] [2]

[1] Specify quantity of emergency sections or emergency generator circuits required based off total length of run. Not available with 347V.

[2] For North America, the minimum emergency system wattage is 10W. Refer to the fixture's lumens per watt to estimate emergency light output. The emergency system typically powers only a portion of the fixture, depending on the fixture configuration and number of drivers. Consult factory for emergency system configuration and illuminated section details.
For Europe, the emergency system wattage and configuration may vary. Consult factory for details.

Note: A drawing will be required at the time of ordering to determine the required location of the emergency sections or generator circuits.

CHICAGO PLENUM

CP0 Not required

CP1 Chicago Plenum [1]

© 2026 Beta-Calco Inc. Specifications are subject to change without notice