





BOGGLE™


SHORT SPECIFICATION SHEET



FIXTURE TYPE



FIXTURE CODE



QUANTITIES

1 HOW TO ORDER

<p>LUMINAIRE</p> <p>BGGRIR Direct</p> <p>One power cord for every 50 linear feet.</p>	<p>LENGTH OF RUN</p> <p>Order in 2ft increments.</p> <p>SFA _ _ _ _</p>	<p>MAX LENGTH PER SECTION</p> <p>SL02 2ft¹</p> <p>SL04 4ft</p> <p>SL06 6ft</p> <p>SL08 8ft</p> <p>SL10 10ft</p> <p>SL12 12ft</p> <p>¹ Not available with 200 lm/ft.</p> <p>* You can select the preferred maximum length per segment, to account for transportation and building constraints. Example: If a 40ft run is required and SL12 (12ft) is selected, we would provide 4x 10ft segments. For special requirements, please contact sales@betacalco.com.</p> <p>* Review the Linear Length Configurations document for each length of run.</p>	
<p>LOUVER</p> <p>BL1 White Glossy</p> <p>BL2 Black Glossy</p> <p>BL3 White Matte</p> <p>BL4 Black Matte</p> <p>All data shown based on max values, consult Performance Data download for more details.</p>	<p>LM/FT</p> <p>LPF020 200 lm/ft</p> <p>LPF040 400 lm/ft</p> <p>LPF060 600 lm/ft</p> <p>LPF080 800 lm/ft</p> <p>LPF100 1000 lm/ft</p>	<p>CRI</p> <p>CR90 CRI 90+</p>	<p>CCT</p> <p>CTA27 2700K</p> <p>CTA30 3000K</p> <p>CTA35 3500K</p> <p>CTA40 4000K</p> <p>CTA60 Tunable White¹</p> <p>¹ Consult factory.</p>

<p>VOLTAGE</p> <p>V1 120/277V V2 240V ¹ V3 347V ² V4 Low Voltage ³</p> <p>¹ Not available in North America. ² Only available with DA01 dimming. ³ Only available with DA45 dimming.</p>	<p>DIMMING</p> <p>DA01 0-10V Dimming 1.0% DA02 0-10V Dimming 0.1% ¹ DA20 DALI Dimming 0.1% ¹ DA21 DALI Dimming 1.0% ¹ DA30 DSI/switchDim ² DA45 PoE ³</p> <p>¹ Not available with V3. ² Not available in North America. Not available with CTA60 (Tunable white). ³ Only available with V4.</p>	<p>CEILING TYPE & TRIM</p> <p>RT1 Tegular T-Bar ¹ RT2 Lay-In T-Bar ¹ RT3 Trimless ³ RT4 Trim ³</p> <p>¹ Fixture designed to fit into a 9/16" or 15/16" standard tegular grid T-bar and through tile mount. Dimensions are nominal for grid ceiling fixtures. All fixture metalwork is white. ² Fixture designed to fit into a 9/16" or 15/16" standard grid T-bar and through tile mount. Dimensions are nominal for grid ceiling fixtures. All fixture metalwork is white. ³ Fixture designed for drywall ceilings.</p>
<p>CEILING TRIM FINISH</p> <p>FA00 Not required FA01 White - Textured ¹ FA02 Black Metallic Textured ¹</p> <p>¹ Required for RT4 only.</p>	<p>EMERGENCY</p> <p>E0 Not required E1 Emergency system - Integral ¹ E3 Emergency generated circuit - Remote ¹</p> <p>¹ A drawing will be required at time of ordering to determine the required number and location of the emergency sections or generator circuits. Not available in 347V. Available upon request, consult factory for details.</p>	<p>CHICAGO PLENUM</p> <p>CP0 Not required CP1 Chicago Plenum ¹</p>