

Project Name:

Fixture Code:

Fixture Type:

Quantities:





## BOX<sup>™</sup> - CEILING

**BOX** is a powerful downlight series with exceptional performance suitable for high ceiling applications. Equipped with high-efficiency reflectors optimized for beam definition and maximum center beam candela power, BOX delivers up to 12,900 lumens. Constructed of aluminum, the robust cuboid fits well with functionalist architecture. Available in single, double, and quad downlights.

#### **GENERAL SPECIFICATION**

**Body and trim** Steel and aluminum.

Mechanical Luminaires mount directly over J box (by others - North America only).

**Drivers** HPF electronic, 120/277V (EU-240V) with 0-10V dimming (1%). The driver is integral to the fixture housing.

#### Reported L70 @25°C (77°F)

>55,000 hrs

Delivered Lumens Delivered lumens & LPW based on 3000K (min 80 CRI).

### **OPTICS & FEATURES**



**Finish** Powder coated.

**Mounting** Surface mount.

Sensors Consult factory regarding sensor compatibility.

**Estimated L70 @25°C (77°F)** >201,000 hrs

**Approvals** Damp Rated.



# BOX™ - CEILING

### HOW TO ORDER

A. LUMINAIRE 751001 1, 3218 lms	<b>751002</b> 2, 6436 lms	<b>751004</b> 4, 12872 lms	
<b>B. CCT</b> <b>30</b> 3000K (min 80 CRi)	<b>35</b> 3500K (min 80 CRi)	<b>40</b> 4000K (min 80 CRi)	
<b>C. REFLECTOR</b> <b>NB</b> Narrow Beam (14°)	<b>MB</b> Medium Beam (22°)	<b>WB</b> Wide Beam (38°)	
<b>D. FINISH</b> BL Black	MS Silver Metallic	<b>WH</b> White	
E. DIMMING D1 0-10V Dimming (1%) L1 Lutron L3DA3W Hi-Lume 1%, 3 Wire	<b>D2</b> 0-10V Dimming (0.1%)	<b>DA</b> DALI Dimming (0.1%)	<b>DL</b> DALI Dimming (1%)

# BOX™ - CEILING

### **TECHNICAL DATA**

### LUMINAIRE

Code	751001	751002	751004
Power (LED)	37W	74W	148W
Heads	1	2	4
Delivered Ims	3218	6436	12872
LPW	84	84	84

### APPROVALS







### DIMENSIONAL DIAGRAMS

