Project Name:

Fixture Code:

Fixture Type:

Quantities:











BOX[™] - SUSPENDED

BOX is a powerful downlight series with exceptional performance suitable for high ceiling applications. Equipped with high-efficiency reflectors optimized for beam definition and maximum center beam candela power, BOX delivers up to 12,900 lumens. Constructed of aluminum, the robust cuboid fits well with functionalist architecture. Available in single, double, and quad downlights.

GENERAL SPECIFICATION

Body and trim Steel and aluminum.

Power cable Silver braided.

Drivers Integral, HPF electronic drivers 120/277V (EU-240V), 0-10V, 10% dimming. The driver is integral to the fixture housing.

Reported L70 @25°C (77°F)

>55,000 hrs

Delivered Lumens Delivered lumens & LPW based on 3000K (min 80 CRI).

OPTICS & FEATURES



Suspended Direct

Finish Powder coated.

Mechanical Luminaires mount directly over J box (by others - North America only).

Sensors Consult factory regarding sensor compatibility.

Estimated L70 @25°C (77°F) >201,000 hrs

Approvals Damp Rated.



HOW TO ORDER

A. LUMINAIRE 751011 1, 3218 lms	751012 2, 6436 lms	751014 4, 12872 lms	
B. CCT 30 3000K (min 80 CRI)	35 3500K (min 80 CRI)	40 4000K (min 80 CRI)	
C. REFLECTOR NB Narrow Beam (14°)	MB Medium Beam (22°)	WB Wide Beam (38°)	
D. FINISH BL Black	MS Silver Metallic	WH White	
E. DIMMING D1 0-10V dimming (1%) L1 Lutron L3DA3W Hi-Lume 1%, 3 Wire	D2 0-10V Dimming (0.1%)	DA DALI dimming (0.1%)	DL DALI dimming (1%)

BOX[™] - SUSPENDED

TECHNICAL DATA

LUMINAIRE

Code	751011	751012	751014
Power (LED)	37W	74W	148W
Heads	1	2	4
Delivered Ims	3218	6436	12872
LPW	84	84	84

APPROVALS





DIMENSIONAL DIAGRAMS

