

CERCHIO II™ - SUSPENDED

Project Name:	Fixture Type:
Fixture Code:	Quantities:



CERCHIO II™ - SUSPENDED



CERCHIO II™ - SUSPENDED

Cerchio II epitomizes contemporary design with elegant clean lines and a floating inner ring that evokes an impression of levity. The outer and inner rings can each have their own finish to make Cerchio II more complementary to surrounding color themes. Cerchio II is also available with an acoustic panel in 13 finishes which adds another decorative dimension while offering sound-absorbing functionality.

GENERAL SPECIFICATION

Body

Aluminum.

Suspension

Stainless steel cables.

Remote emergency

Emergency option provides a 1.5 hour (3 hours for EU) emergency lighting facility. The remote system includes the inverter module, NiCad batteries and a remote wall/ceiling LED charge indicator and test switch (NA only) Maximum distance between wall/ceiling plate and luminaire is 4.5m/15'. Test switch fits a single gang box (not supplied).

Drivers

HPF electronic drivers for 120-277V, 347V (EU-240V). Depending on options selected, driver can be either integral in the canopy or remotely mounted.

Acoustic Panels NRC Rating

0.80

Acoustic Panels Material

100% recycled polyester fiber (PET).

PoE

Cerchio II can integrate into your data network via Power over Ethernet (PoE) connectivity.

L70 @25°C

>50,000 hrs.

Approvals

Damp Rated.

Acoustic Panel Maintenance

Durable and easy to maintain. Dust regularly and clean marks with mild detergent, rinse, and blot.

Finish

Powder coated.

Power cable

Silver braided.

Remote mounting of drivers

Wire Size 18 AWG - Max distance (from canopy to drivers) 9.5', Wire size 16 AWG - Max distance 19.5', Wire size 14 AWG - Max distance 29.5'. Drivers must be accessible after installation. 5ft(1524mm) and above c/w 2 remote driver boxes and 2 power cords.

Mechanical

Luminaires mount directly over J box (by others - North America only).

Acoustic Panels Fire Rating

ASTM E84-2018 Class A.

Acoustic Panels Thickness

12mm (0.5")

Sensors

Consult factory regarding sensor compatibility.

Delivered lumens

Delivered lumens & LPW based on 4000K (min 80 CRI).

Seismic Bracing

Seismic bracing kits are available to meet compliance requirements. Consult the factory for details.



CERCHIO II™ - SUSPENDED

OPTICS & FEATURES



Suspended Direct/Indirect



Acoustic



Direct-indirect



Declare



PoE

CERCHIO II™ - SUSPENDED

HOW TO ORDER

A. LUMINAIRE

CERP1P02 2ft, 4200 lumens	CERP1P03 3ft, 6700 lumens	CERP1P04 4ft, 9200 lumens	CERP1P05 5ft, 11600 lumens
CERP1P06 6ft, 13900 lumens	CERP1P07 7ft, 16300 lumens		

B. LUMENS/FT

LPF035 350 lm/ft ¹	LPF052 525 lm/ft ²	LPF070 700 lm/ft ³	
--------------------------------------	--------------------------------------	--------------------------------------	--

¹ Based of 50% of total output.
² Based on 75% of total output.
³ 100% of total output.

C. CRI

CR80 CRI 80+	CR90 CRI 90+		
---------------------	---------------------	--	--

D. CCT

CTA27 2700K	CTA30 3000K	CTA35 3500K	CTA40 4000K
--------------------	--------------------	--------------------	--------------------

E. VOLTAGE

V1 120/277V	V2 240V ¹	V3 347V ²	V4 Low voltage ³
--------------------	-----------------------------	-----------------------------	------------------------------------

¹ V2 not available in North America.
² V3 available with DA01 dimming only.
³ V4 available with DA45 dimming only.

F. DIMMING (REMOTE)

DA01 0-10V Dimming 1.0%	DA02 0-10V Dimming 0.1% ¹	DA10 0-10V Dimming 10.0%	DA20 DALI Dimming 0.1% ¹
DA21 DALI Dimming 1.0% ¹	DA45 PoE ²		

¹ Not available with V3 or V4.
² DA45 used V4 only.

G. SUSPENSION

SS1 Vertical, Remote driver	SS2 Hub, Remote driver	SS3 Vertical, Driver Integral to Canopy ¹	SS4 Hub, Driver Integral to Canopy ¹
------------------------------------	-------------------------------	---	--

¹ Available up to 4ft diameter.

H. FINISH INNER RING

FA01 White	FA02 Black Metallic - Textured	FA20 Silver Metallic - Textured	FA25 Gold Metallic - Textured
FA44 Midnight Blue Metallic - Textured	FA45 Copper Metallic	FA46 Charcoal Metallic - Textured	FA47 Bronze Metallic - Textured
FA52 Champagne Metallic	FA53 Red Metallic - Textured		

I. FINISH OUTER RING

FB01 White	FB02 Black Metallic - Textured	FB20 Silver Metallic - Textured	FB25 Gold Metallic - Textured
FB44 Midnight Blue Metallic - Textured	FB45 Copper Metallic	FB46 Charcoal Metallic - Textured	FB47 Bronze Metallic - Textured
FB52 Champagne Metallic	FB53 Red Metallic - Textured		

CERCHIO II™ - SUSPENDED

J. CANOPY FINISH

CF01 White	CF02 Black Metallic - Textured	CF20 Silver Metallic - Textured	CF25 Gold Metallic - Textured
CF44 Midnight Blue Metallic - Textured	CF45 Copper Metallic	CF46 Charcoal Metallic - Textured	CF47 Bronze Metallic - Textured
CF52 Champagne Metallic	CF53 Red Metallic - Textured		

K. ACOUSTIC PANEL COLORS

AP00 Not required	AP02 Citrus	AP04 White	AP08 Red Coffee
AP11 Light Gray	AP13 Apple Green	AP22 Blue	AP26 Sesame Gray
AP27 Black	AP47 Navy Peony	AP60 Pure Red	AP73 Cloudburst
AP89 Douglas Fir	APW01 Oak		

Diameters from 60" to 84" include a visible seam.

For accompanying non-illuminating acoustic panels see our Acoustic Circles, Quads and Triangles spec pages.

Contact factory for additional colors.

L. EMERGENCY

E0 Not required	E2 Emergency system - Remote
------------------------	-------------------------------------


CERCHIO II™ - SUSPENDED

TECHNICAL DATA


LUMINAIRE

Code	CERP1P02	CERP1P03	CERP1P04	CERP1P05	CERP1P06	CERP1P07
Diameter (A)	2ft	3ft	4ft	5ft	6ft	7ft
Wattage	38	60	83	105	125	147
Delivered lms	4200	6700	9200	11600	13900	16300
LPW	111	111	111	111	111	111
# of Sections	1	1	1	1	1	1
Suspension Points	3	3	3	6	6	6


FINISH INNER RING




White




Black Metallic -
Textured




Silver Metallic -
Textured




Gold Metallic -
Textured




Midnight Blue Metallic -
Textured




Copper Metallic




Charcoal Metallic -
Textured



Bronze Metallic -
Textured




Champagne Metallic




Red Metallic -
Textured


FINISH OUTER RING




White




Black Metallic -
Textured




Silver Metallic -
Textured




Gold Metallic -
Textured




Midnight Blue Metallic -
Textured




Copper Metallic




Charcoal Metallic -
Textured



Bronze Metallic -
Textured











Champagne Metallic





Red Metallic -
Textured









CERCHIO II™ - SUSPENDED







FINISH CANOPY

							
White	Black Metallic - Textured	Silver Metallic - Textured	Gold Metallic - Textured	Midnight Blue Metallic - Textured	Copper Metallic	Charcoal Metallic - Textured	Bronze Metallic - Textured

	
Champagne Metallic	Red Metallic - Textured

ACOUSTIC PANEL COLORS

							
Not required	Citrus	White	Red Coffee	Light Gray	Apple Green	Blue	Sesame Gray

					
Black	Navy Peony	Pure Red	Cloudburst	Douglas Fir	Oak

Diameters from 60" to 84" include a visible seam.

For accompanying non-illuminating acoustic panels see our Acoustic Circles, Quads and Triangles spec pages.

Contact factory for additional colors.


APPROVALS




CERCHIO II™ - SUSPENDED

DIMENSIONAL DIAGRAMS


SS1
Vertical - Remote Driver




SS3
Vertical - Integral Driver



SS2
Hub - Remote Driver




SS4
Hub - Integral Driver



Code	Diameter (A)
CERP1P02	2' [610mm]
CERP1P03	3' [914mm]
CERP1P04	4' [1219mm]
CERP1P05	5' [1524mm]
CERP1P06	6' [1829mm]
CERP1P07	7' [2134mm]

CERCHIO II™ - SUSPENDED



Code	Diameter (A)
CERP1P02	2' [610mm]
CERP1P03	3' [914mm]
CERP1P04	4' [1219mm]
CERP1P05	5' [1524mm]
CERP1P06	6' [1829mm]
CERP1P07	7' [2134mm]