

BORDER™ - INGROUND EXTERIOR

Project Name:

Fixture Type:

Fixture Code:

Quantities:



BORDER™ - INGROUND EXTERIOR

GENERAL SPECIFICATION

Body and trim

Low copper, die-cast aluminum highly resistant to oxidation.

Bezel

Stainless steel.

Finish

Double powder coating polyester high resistant to UV and oxidation.

External screws

A4 stainless steel treated with highly antioxidant water-repellent lubricating solution to ensure easy opening.

Drivers

HPF, electronic 120/277V.

Rough-in housing

Thermoplastic.

Lens

8mm/0.3" tempered glass.

Gasket

Silicone.

Reflectors

High purity aluminum.

Cable entry

M20 cable gland for DIA 6-12mm/0.24-0.47" cables.

Walk over

Static pressure load 500Kg/1100lbs.

Mechanical

For in-ground or wall installation in poured concrete or brick.

OPTICS & FEATURES



Ext-Inground



Medium

BORDER™ - INGROUND EXTERIOR

HOW TO ORDER

A. LUMINAIRE

8107228 8107228

8107230 8107230

8107232 8107232

8107234 8107234

B. CCT

30 3000K (min 80 CRI)

40 4000K (min 80 CRI)

C. OPTIONS

SC Second Cable Entry

DB Dimming (0-10V, 10%)

D. ROUGH-IN HOUSING (REQUIRED)

RIH280 Rough-In Housing for 15"
Luminaires

RIH281 Rough-In Housing for 25"
Luminaires

RIH282 Rough-In Housing for 37"
Luminaires

RIH283 Rough-In Housing for 48.5"
Luminaires

TECHNICAL DATA

LUMINAIRE

Code	8107228	8107230	8107232	8107234
Power (LED)	9W	18W	27W	36W
Distribution	Medium 24	Medium 24	Medium 24	Medium 24
Delivered lms	990	1980	2957	3959
Length (A)	15"	25"	37"	48.5"

APPROVALS



BORDER™ - INGROUND EXTERIOR

DIMENSIONAL DIAGRAMS

