

# BORDER™ - INGROUND EXTERIOR

Project Name:

Fixture Type:

Fixture Code:

Quantities:



# BORDER™ - INGROUND EXTERIOR

## GENERAL SPECIFICATION

### Body and trim

Low copper, die-cast aluminum highly resistant to oxidation.

### Bezel

Stainless steel.

### Finish

Double powder coating polyester high resistant to UV and oxidation.

### External screws

A4 stainless steel treated with highly antioxidant water-repellent lubricating solution to ensure easy opening.

### Drivers

HPF, electronic 120/277V.

### Rough-in housing

Thermoplastic.

### Lens

8mm/0.3" tempered glass.

### Gasket

Silicone.

### Reflectors

High purity aluminum.

### Cable entry

M20 cable gland for DIA 6-12mm/0.24-0.47" cables.

### Walk over

Static pressure load 500Kg/1100lbs.

### Mechanical

For in-ground or wall installation in poured concrete or brick.

## OPTICS & FEATURES



Ext-Inground



Medium

# BORDER™ - INGROUND EXTERIOR

## HOW TO ORDER

### A. LUMINAIRE

**8107228** 8107228                      **8107230** 8107230                      **8107232** 8107232                      **8107234** 8107234

### B. CCT

**30** 3000K (min 80 CRI)                      **40** 4000K (min 80 CRI)

### C. OPTIONS

**SC** Second Cable Entry                      **DB** Dimming (0-10V, 10%)

### D. ROUGH-IN HOUSING (REQUIRED)

**RIH280** Rough-In Housing for 15" Luminaires                      **RIH281** Rough-In Housing for 25" Luminaires                      **RIH282** Rough-In Housing for 37" Luminaires                      **RIH283** Rough-In Housing for 48.5" Luminaires

## TECHNICAL DATA

### LUMINAIRE

Code	8107228	8107230	8107232	8107234
Power (LED)	9W	18W	27W	36W
Distribution	Medium 24	Medium 24	Medium 24	Medium 24
Delivered lms	990	1980	2957	3959
Length (A)	15"	25"	37"	48.5"

## APPROVALS



# BORDER™ - INGROUND EXTERIOR

## DIMENSIONAL DIAGRAMS

